

View Online at <https://aerobasegroup.com/nsn/6105-01-171-4539>

Overall Height:

9.880 inches

Overall Length:

20.820 inches

Overall Width:

12.250 inches

Thread Length:

0.8800 inches single end

Step Diameter:

0.8740 inches single end

Step Length:

0.7500 inches single end

Keyway Width:

0.1240 inches single end

Keyway Depth:

0.0620 inches single end

Shaft Diameter:

0.375 inches single end

Keyway Length:

0.9400 inches single end

Shaft Rotation Direction:

Clockwise single end

Duty Cycle:

Continuous

Inclosure Feature:

Totally enclosed

Winding Type:

Induction-squirrel cage

Mounting Method:

Fixed base and face

Mounting Facility Type And Quantity:

8 unthreaded hole

Cooling Method:

Fan cooled

Current Rating Method:

Load

Inclosure Specification:

Nema

Features Provided:

Horizontal mounting position

Frame Size Designation:

184tncz

Power Rating:

3.0000 horsepower output

Thread Size:

0.375 inches single end

Length Of Shaft From Housing:

7.060 inches single end

Shaft Center To Mounting Surface Distance:

4.485 inches single end

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.500 inches

Tempurature Rating:

50.0 operating degrees celsius

Mounting Facility Circle Diameter:

7.250 inches

Rotor Speed Rating In Rpm:

3600.0 single no load and 3500.0 single full load

Center To Center Distance Between Mounting Facilities Parallel To Width:

7.500 inches

Current Rating In Amps:

4.360 single input

Connection Type And Voltage Rating In Volts:

440.0 line to neutral single input

Shaft End Characteristic:

A2 first style single end and a9 second style single end and a1 third style single end and a12 fourth style single end

Phase:

Three input

Special Features:

Shaft end second style 0.500 in. Dia; shaft end third style 0.624 in. Dia; shaft end fourth style 1.062 in. Dia

Frequency In Hertz:

60.0 input

Thread Series Designator:

Unf single end

Terminal Type And Quantity:

3 solderless lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0