NSN 6105-01-208-1026

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-208-1026 **Overall Height:** 45.062 inches **Overall Length:** 41.750 inches **Overall Width:** 25.500 inches Thread Length: 0.750 inches single end **Taper Length:** 1.750 inches single end **Keyway Width:** 0.375 inches single end **Keyway Depth:** 0.188 inches single end **Shaft Diameter:** 0.939 inches single end **Keyway Length:** 1.750 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Totally enclosed Winding Type: Induction-squirrel cage **Mounting Method:** Face **Mounting Facility Type And Quantity:** 8 unthreaded hole **Cooling Method:** Fan cooled **Current Rating Method:** Load **Inclosure Specificationification:** Nema Frame Size Designation: 445unpz **Power Rating:** 100.000 horsepower input Taper:

1.250 per foot in inches single end

NSN 6105-01-208-1026Alternating Current Motor - Page 2 of 2



Length Of Shaft From Housing:
4.500 inches single end
Shaft Center To Mounting Surface Distance:
9.000 inches single end
Tempurature Rating:
50.0 operating degrees celsius
Mounting Facility Circle Diameter:
13.500 inches
Rotor Speed Rating In Rpm:
1800.0 single no load
Current Rating In Amps:
120.000 single input
Connection Type And Voltage Rating In Volts:
440.0 line to line single input
Shaft End Characteristic:
A2 first style single end and a29 second style single end and a1 third style single end
Phase:
Three input
Special Features:
0.969 in. Diameter w/32 thd per in. By 0.750 in. Lg, w/0.188 in. W, by 0.625 in. Lg key, 0.094 in. Deep on style a2 shaft
Frequency In Hertz:
60.0 input
Terminal Type And Quantity:
3 solderless lug and 3 wire lead
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A271a0