

NSN 6105-01-220-0514 Alternating Current Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6105-01-220-0514 **Thread Class:** 2a single end **Thread Direction:** Right-hand single end **Overall Height:** 7.000 inches **Overall Length:** 13.875 inches **Overall Width:** 7.000 inches Thread Length: 0.875 inches single end **Keyway Width:** 0.188 inches single end **Keyway Depth:** 0.094 inches single end **Shaft Diameter:** 0.500 inches single end **Keyway Length:** 2.125 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Continuous

Inclosure Feature:

Spray tight and totally enclosed

Winding Type:

Induction-squirrel cage

Mounting Method:

Face

Mounting Facility Type And Quantity:

4 threaded hole

Cooling Method:

Natural convection ventilated

Current Rating Method:

Load

Inclosure Specificationification:

Nema

Frame Size Designation:

561

Power Rating:

0.750 horsepower output

NSN 6105-01-220-0514Alternating Current Motor - Page 2 of 2



Thread Size:
0.500 inches single end
Length Of Shaft From Housing:
3.500 inches single end
Tempurature Rating:
65.0 ambient degrees celsius
Mounting Facility Circle Diameter:
5.875 inches
Rotor Speed Rating In Rpm:
3520.0 single no load
Current Rating In Amps:
1.400 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a9 second style single end and a1 third style single end
Phase:
Three input
Special Features:
Shaft first style has 0.125 in. Diameter through hole; shaft second style keyway extends across first style; shaft second style 0.625 in. Dia;
shaft third style 0.750 in. Min, 0.755 in. Maximum dia
Frequency In Hertz:
60.0 input
Thread Series Designator:
Unc single end
Terminal Type And Quantity:
3 solderless lug and 3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0