Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-222-2153

Overall Height: 25.120 inches Overall Length: 42.880 inches Overall Width: 30.880 inches Keyway Width: 0.620 inches identical ends Keyway Depth: 0.320 inches identical ends Shaft Diameter:
42.880 inches Overall Width: 30.880 inches Keyway Width: 0.620 inches identical ends Keyway Depth: 0.320 inches identical ends
42.880 inches Overall Width: 30.880 inches Keyway Width: 0.620 inches identical ends Keyway Depth: 0.320 inches identical ends
30.880 inches Keyway Width: 0.620 inches identical ends Keyway Depth: 0.320 inches identical ends
Keyway Width: 0.620 inches identical ends Keyway Depth: 0.320 inches identical ends
0.620 inches identical ends Keyway Depth: 0.320 inches identical ends
Keyway Depth: 0.320 inches identical ends
0.320 inches identical ends
Shaft Diameter:
Shart Diameter.
2.375 inches second end
Keyway Length:
5.500 inches second end
Shaft Rotation Direction:
Clockwise or counterclockwise identical ends
Duty Cycle:
Intermittent
Inclosure Feature:
Dripproof protected-15 deg
Winding Type:
Induction-squirrel cage
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
4 unthreaded hole
Current Rating Method:
Load
Inclosure Specificationification:
Nema
Features Provided:
Horizontal mounting position
Frame Size Designation:
445unz
Power Rating:
8.300 horsepower or 50.000 horsepower output
Length Of Shaft From Housing:
7.560 inches second end
Shaft Center To Mounting Surface Distance:
10.970 inches identical ends
Center To Center Distance Between Mounting Facilities Parallel To Length:
16.500 inches
7.560 inches second end Shaft Center To Mounting Surface Distance:

NSN 6105-01-222-2153

Alternating Current Motor - Page 2 of 2



Tempurature Rating:
40.0 ambient degrees celsius
Rotor Speed Rating In Rpm:
300.0 low no load and 1800.0 high no load and 260.0 low full load and 1695.0 high full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
18.000 inches
Current Rating In Amps:
45.000 low or 60.000 high input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A9 first style and a1 second style second end
Phase:
Three input
Special Features:
Shaft ends second style 2.437 in. Dia
Frequency In Hertz:
60.0 input
Terminal Type And Quantity:
6 solderless lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A271a0