NSN 6105-01-231-5450

Overall Height: 16.180 inches Overall Length: 26.120 inches Overall Width: 19.500 inches

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-231-5450

1.520 inches single end Shaft Diameter: 1.562 inches single end Duty Cycle: Continuous Inclosure Feature: Spray tight Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end Phase:	Thread Length:
1.562 inches single end Duty Cycle: Continuous Inclosure Feature: Spray tight Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	1.520 inches single end
Continuous Inclosure Feature: Spray tight Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Shaft Diameter:
Inclosure Feature: Spray tight Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	1.562 inches single end
Inclosure Feature: Spray tight Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Duty Cycle:
Spray tight Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Continuous
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Inclosure Feature:
Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Spray tight
Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Winding Type:
Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Induction-squirrel cage
Mounting Facility Type And Quantity: 4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Mounting Method:
4 threaded hole Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Face
Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Mounting Facility Type And Quantity:
Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	4 threaded hole
Inclosure Specificationification: Nema Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Current Rating Method:
Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Load
Frame Size Designation: 256tny Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Inclosure Specificationification:
Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Nema
Power Rating: 4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Frame Size Designation:
4.500 horsepower output or 15.000 horsepower output Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	256tny
Length Of Shaft From Housing: 6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Power Rating:
6.620 inches single end Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	4.500 horsepower output or 15.000 horsepower output
Tempurature Rating: 65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Length Of Shaft From Housing:
65.0 ambient degrees celsius Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	6.620 inches single end
Mounting Facility Circle Diameter: 12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Tempurature Rating:
12.500 inches Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	65.0 ambient degrees celsius
Current Rating In Amps: 7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Mounting Facility Circle Diameter:
7.300 low input or 20.000 high input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	12.500 inches
Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	Current Rating In Amps:
440.0 line to neutral single input Shaft End Characteristic: A2 single style single end and a1 second style single end	7.300 low input or 20.000 high input
Shaft End Characteristic: A2 single style single end and a1 second style single end	Connection Type And Voltage Rating In Volts:
A2 single style single end and a1 second style single end	440.0 line to neutral single input
	Shaft End Characteristic:
Phase:	A2 single style single end and a1 second style single end
	Phase:
Three input	Three input

NSN 6105-01-231-5450

Alternating Current Motor - Page 2 of 2



Special Features:
Shaft end second style 1.754 in. Dia
Frequency In Hertz:
60.0 input
Terminal Type And Quantity:
3 solderless lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A271a0