## NSN 6105-01-233-1762

Alternating Current Motor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6105-01-233-1762



**Thread Class:** 2b single end **Thread Direction:** Right-hand single end **Overall Height:** 10.750 inches **Overall Length:** 21.190 inches **Overall Width:** 10.750 inches Thread Length: 1.130 inches single end **Keyway Width:** 0.250 inches single end **Keyway Depth:** 0.125 inches single end **Shaft Diameter:** 1.000 inches single end **Keyway Length:** 1.250 inches single end **Shaft Rotation Direction:** Clockwise or counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Spray tight Winding Type: Induction-squirrel cage **Mounting Method:** Face **Mounting Facility Type And Quantity:** 8 threaded hole **Cooling Method:** Ambient air **Current Rating Method:** Load **Inclosure Specificationification:** Nema Frame Size Designation: 215tncz **Power Rating:** 0.950 horsepower or 7.500 horsepower output

## NSN 6105-01-233-1762

Alternating Current Motor - Page 2 of 2



Thread Size:
1.000 inches single end
Length Of Shaft From Housing:
5.690 inches single end
Tempurature Rating:
65.0 ambient degrees celsius
Mounting Facility Circle Diameter:
7.250 inches
Rotor Speed Rating In Rpm:
1800.0 low no load and 3600.0 high no load and 1760.0 low full load and 3530.0 high full load
Current Rating In Amps:
2.200 low or 9.200 high input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style and a9 second style and a1 third style single end
Phase:
Three input
Special Features:
Shaft end first style has 0.203 in. Diameter drill through hole; shaft end second style 1.124 in. Min, 1.125 in. Maximum dia; shaft end third
style 1.374 in. Min, 1.375 in. Maximum dia
Frequency In Hertz:
60.0 input
Thread Series Designator:
Unc single end
Terminal Type And Quantity:
6 solderless lug and 6 wire lead
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A271a0