NSN 6105-01-237-7478

Alternating Current Motor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6105-01-237-7478 |
|---|
| Overall Height: |
| 15.500 inches |
| Overall Length: |
| 27.875 inches |
| Overall Width: |
| 18.188 inches |
| Keyway Width: |
| 0.375 inches single end |
| Keyway Depth: |
| 0.188 inches single end |
| Shaft Diameter: |
| 1.624 inches single end and 1.625 inches single end |
| Keyway Length: |
| 4.000 inches single end |
| Shaft Rotation Direction: |
| Clockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Spray tight |
| Winding Type: |
| Induction-squirrel cage |
| Mounting Method: |
| Fixed base |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Cooling Method: |
| Fan cooled |
| Current Rating Method: |
| Load |
| Inclosure Specificationification: |
| Nema |
| Frame Size Designation: |
| 324a Power Rating: |
| - |
| 2.750 horsepower output or 5.000 horsepower output |
| Length Of Shaft From Housing: |

4.875 inches single end

Shaft Center To Mounting Surface Distance:

8.000 inches single end

Center To Center Distance Between Mounting Facilities Parallel To Length:

10.500 inches

NSN 6105-01-237-7478

Fiig: A271a0

Alternating Current Motor - Page 2 of 2



| Tempurature Rating: |
|---|
| 65.0 ambient degrees celsius |
| Rotor Speed Rating In Rpm: |
| 900.0 low no load and 1200.0 high no load and 850.0 low full load and 1150.0 high full load |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 12.500 inches |
| Current Rating In Amps: |
| 4.500 low input or 7.500 high input |
| Connection Type And Voltage Rating In Volts: |
| 440.0 line to neutral single input |
| Shaft End Characteristic: |
| A9 single style single end |
| Phase: |
| Three input |
| Frequency In Hertz: |
| 60.0 input |
| Terminal Type And Quantity: |
| 6 solderless lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |