NSN 6105-01-274-5505

Alternating Current Motor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6105-01-274-5505 |
|---|
| Overall Height: |
| 9.880 inches |
| Overall Length: |
| 14.620 inches |
| Overall Width: |
| 13.380 inches |
| Keyway Width: |
| 0.250 inches single end |
| Keyway Depth: |
| 0.125 inches single end |
| Shaft Diameter: |
| 1.125 inches single end |
| Keyway Length: |
| 1.750 inches single end |
| Shaft Rotation Direction: |
| Clockwise single end or counterclockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Totally enclosed |
| Winding Type: |
| Induction-squirrel cage |
| Mounting Method: |
| Fixed base |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Cooling Method: |
| Fan cooled |
| Current Rating Method: |
| Load |
| Inclosure Specificationification: |
| Nema |
| Features Provided: |
| Horizontal mounting position |
| Frame Size Designation: |
| 182tn |

Power Rating:

2.000 horsepower output

Length Of Shaft From Housing:

2.810 inches single end

Shaft Center To Mounting Surface Distance:

4.500 inches single end

NSN 6105-01-274-5505

Alternating Current Motor - Page 2 of 2



| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
|---|--|
| 4.500 inches | |
| Tempurature Rating: | |
| 50.0 ambient degrees celsius | |
| Rotor Speed Rating In Rpm: | |
| 1800.0 single no load and 1760.0 single full load | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | |
| 7.500 inches | |
| Current Rating In Amps: | |
| 3.000 single input | |
| Connection Type And Voltage Rating In Volts: | |
| 440.0 line to neutral single input | |
| Shaft End Characteristic: | |
| A9 single style single end | |
| Phase: | |
| Three input | |
| Frequency In Hertz: | |
| 60.0 input | |
| Terminal Type And Quantity: | |
| 3 solderless lug | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A271a0 | |