Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-316-6850

Thread Class:

2b single end

Thread Direction:

Right-hand single end

Overall Height:

13.250 inches

Overall Length:

23.250 inches

Overall Width:

13.500 inches

Thread Length:

1.000 inches single end

Keyway Width:

0.250 inches single end

Keyway Depth:

0.252 inches single end

Shaft Diameter:

1.2490 inches single end and 1.2495 inches single end

Keyway Length:

2.500 inches single end

Shaft Rotation Direction:

Clockwise single end or counterclockwise single end

Duty Cycle:

Continuous

Inclosure Feature:

Dripproof protected-15 deg

Winding Type:

Induction-squirrel cage

Mounting Method:

Fixed base

Mounting Facility Type And Quantity:

4 unthreaded hole

Cooling Method:

Self-ventilated

Current Rating Method:

Load

Inclosure Specificationification:

Mil-std-108

Features Provided:

Horizontal mounting position

Frame Size Designation:

215tn



Power Rating:	
10.000 horsepov	wer output
Thread Size:	
0.500 inches sin	igle end
Length Of Shaf	t From Housing:
8.130 inches sin	gle end
Shaft Center To	o Mounting Surface Distance:
5.235 inches sin	gle end
Center To Cent	er Distance Between Mounting Facilities Parallel To Length:
7.000 inches	
Tempurature R	ating:
50.0 ambient de	grees celsius
Rotor Speed Ra	ating In Rpm:
3530.0 single fu	ll load
Center To Cent	er Distance Between Mounting Facilities Parallel To Width:
8.500 inches	
Current Rating	In Amps:
12.500 single in	put
Connection Ty	pe And Voltage Rating In Volts:
440.0 line to neu	utral single input
Shaft End Char	acteristic:
A3 first style sing	gle end and a9 second style single end
Phase:	
Three input	
Frequency In H	lertz:
60.0 input	
Thread Series I	Designator:
Unc single end	
Terminal Type	And Quantity:
3 solderless lug	
Fsc Application	n Data:
Air conditioning	chilled water pump
Shelf Life:	
N/a	
Unit Of Measur	e:
Demilitarizatior	n:
No	
Fiig:	
A271a0	
Mil-std (military	/ Standard):
Mil-std-108 spec	D.
·	