

NSN 6105-01-316-6850 Alternating Current Motor - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/6105-01-316-6850
Thread Class:
2b single end
Thread Direction:
Right-hand single end
Overall Height:
13.250 inches
Overall Length:
23.250 inches
Overall Width:
13.500 inches
Thread Length:
1.000 inches single end
Keyway Width:
0.250 inches single end
Keyway Depth:
0.252 inches single end
Shaft Diameter:
1.2490 inches single end and 1.2495 inches single end
Keyway Length:
2.500 inches single end
Shaft Rotation Direction:
Clockwise single end or counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Dripproof protected-15 deg
Winding Type:
Induction-squirrel cage
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
4 unthreaded hole
Cooling Method:

Self-ventilated

**Current Rating Method:** 

Load

**Inclosure Specificationification:** 

Mil-std-108

**Features Provided:** 

Horizontal mounting position

Frame Size Designation:

215tn

## NSN 6105-01-316-6850

Alternating Current Motor - Page 2 of 2



Power Rating:
10.000 horsepower output
Thread Size:
0.500 inches single end
Length Of Shaft From Housing:
8.130 inches single end
Shaft Center To Mounting Surface Distance:
5.235 inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length:
7.000 inches
Tempurature Rating:
50.0 ambient degrees celsius
Rotor Speed Rating In Rpm:
3530.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
8.500 inches
Current Rating In Amps:
12.500 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A3 first style single end and a9 second style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Thread Series Designator:
Unc single end
Terminal Type And Quantity:
3 solderless lug
Fsc Application Data:
Air conditioning chilled water pump
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.