

View Online at <https://aerobasegroup.com/nsn/6105-01-316-6852>

Thread Class:

2b single end

Thread Direction:

Right-hand single end

Overall Height:

24.000 inches

Overall Length:

36.380 inches

Overall Width:

23.685 inches

Thread Length:

1.000 inches single end

Keyway Width:

0.250 inches single end

Keyway Depth:

0.252 inches single end

Shaft Diameter:

1.2490 inches single end and 1.2495 inches single end

Keyway Length:

2.500 inches single end

Shaft Rotation Direction:

Clockwise single end or counterclockwise single end

Duty Cycle:

Continuous

Inclosure Feature:

Submersible-15 foot

Winding Type:

Induction-squirrel cage

Mounting Method:

Fixed base and flange

Mounting Facility Type And Quantity:

4 unthreaded hole and 8 threaded hole

Cooling Method:

Nonventilated

Current Rating Method:

Load

Inclosure Specification:

Mil-std-108

Features Provided:

Horizontal mounting position

Frame Size Designation:

405t

Power Rating:

25.000 horsepower output

Thread Size:

0.500 inches single end

Length Of Shaft From Housing:

2.560 inches single end

Shaft Center To Mounting Surface Distance:

9.970 inches single end

Center To Center Distance Between Mounting Facilities Parallel To Length:

13.750 inches

Tempurature Rating:

50.0 ambient degrees celsius

Rotor Speed Rating In Rpm:

1785.0 single full load

Center To Center Distance Between Mounting Facilities Parallel To Width:

16.000 inches

Current Rating In Amps:

30.000 single input

Connection Type And Voltage Rating In Volts:

440.0 line to neutral single input

Shaft End Characteristic:

A3 first style single end and a9 second style single end

Phase:

Three input

Frequency In Hertz:

60.0 input

Thread Series Designator:

Unc single end

Terminal Type And Quantity:

3 solderless lug

Fsc Application Data:

Electric pwr supply-emer sserv delec eng salt water

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.