NSN 6105-01-317-3652

Overall Height: 26.250 inches

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-317-3652

Overall Length:
34.060 inches
Overall Width:
27.620 inches
Keyway Width:
0.625 inches single end and 0.627 inches single end
Keyway Depth:
0.312 inches single end and 0.314 inches single end
Shaft Diameter:
2.374 inches single end and 2.375 inches single end
Keyway Length:
3.010 inches single end
Shaft Rotation Direction:
Clockwise single end or counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Dripproof protected-15 deg
Winding Type:
Induction-squirrel cage
Mounting Method:
Fixed base
Fixed base Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 unthreaded hole
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method:
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method:
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification:
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided:
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Frame Size Designation:
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Frame Size Designation: 444tnsd
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Frame Size Designation: 444tnsd Power Rating:
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Frame Size Designation: 444tnsd Power Rating: 75.000 horsepower output
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Frame Size Designation: 444tnsd Power Rating: 75.000 horsepower output Length Of Shaft From Housing:
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Frame Size Designation: 444tnsd Power Rating: 75.000 horsepower output Length Of Shaft From Housing: 4.500 inches single end

NSN 6105-01-317-3652Alternating Current Motor - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To Length:
14.500 inches
Tempurature Rating:
50.0 ambient degrees celsius
Rotor Speed Rating In Rpm:
890.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
18.000 inches
Current Rating In Amps:
95.700 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A9 single style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Terminal Type And Quantity:
3 solderless lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.