## NSN 6105-01-319-0129

**Overall Height:** 

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-319-0129

8.281 inches				
Overall Length:				
11.938 inches				
Overall Width:				
6.500 inches				
Undercut Diameter:				
0.803 inches single end and 0.806 inches single end				
Shaft Diameter:				
0.9842 inches single end and 0.9846 inches single end				
Undercut Length:				
0.510 inches single end and 0.520 inches single end				
Duty Cycle:				
Continuous				
Inclosure Feature:				
Dripproof-15 deg				
Mounting Method:				
Fixed base				
Mounting Facility Type And Quantity:				
2 slot				
Current Rating Method:				
Load				
Frame Size Designation:				
Frame Size Designation: L56z				
L56z				
L56z  Power Rating:				
L56z  Power Rating: 0.750 horsepower output				
L56z  Power Rating: 0.750 horsepower output  Length Of Shaft From Housing:				
L56z  Power Rating: 0.750 horsepower output  Length Of Shaft From Housing: 3.022 inches single end				
Power Rating: 0.750 horsepower output Length Of Shaft From Housing: 3.022 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:				
Power Rating: 0.750 horsepower output Length Of Shaft From Housing: 3.022 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches				
Power Rating: 0.750 horsepower output Length Of Shaft From Housing: 3.022 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches Rotor Speed Rating In Rpm:				
Power Rating: 0.750 horsepower output Length Of Shaft From Housing: 3.022 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches Rotor Speed Rating In Rpm: 1725.0 single full load				
Power Rating: 0.750 horsepower output  Length Of Shaft From Housing: 3.022 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches  Rotor Speed Rating In Rpm: 1725.0 single full load  Center To Center Distance Between Mounting Facilities Parallel To Width:				
Power Rating: 0.750 horsepower output Length Of Shaft From Housing: 3.022 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 4.875 inches				
Power Rating: 0.750 horsepower output Length Of Shaft From Housing: 3.022 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 4.875 inches Current Rating In Amps:				
Power Rating: 0.750 horsepower output  Length Of Shaft From Housing: 3.022 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches  Rotor Speed Rating In Rpm: 1725.0 single full load  Center To Center Distance Between Mounting Facilities Parallel To Width: 4.875 inches  Current Rating In Amps: 5.400 first multiple input or 10.800 second multiple input				
Power Rating: 0.750 horsepower output Length Of Shaft From Housing: 3.022 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 4.875 inches Current Rating In Amps: 5.400 first multiple input or 10.800 second multiple input Connection Type And Voltage Rating In Volts:				
Power Rating: 0.750 horsepower output Length Of Shaft From Housing: 3.022 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 4.875 inches Current Rating In Amps: 5.400 first multiple input or 10.800 second multiple input Connection Type And Voltage Rating In Volts: 230.0 line to neutral first multiple input or 115.0 line to neutral second multiple input				
Power Rating: 0.750 horsepower output  Length Of Shaft From Housing: 3.022 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length: 3.000 inches  Rotor Speed Rating In Rpm: 1725.0 single full load  Center To Center Distance Between Mounting Facilities Parallel To Width: 4.875 inches  Current Rating In Amps: 5.400 first multiple input or 10.800 second multiple input  Connection Type And Voltage Rating In Volts: 230.0 line to neutral first multiple input or 115.0 line to neutral second multiple input  Shaft End Characteristic:				
Power Rating:  0.750 horsepower output  Length Of Shaft From Housing:  3.022 inches single end  Center To Center Distance Between Mounting Facilities Parallel To Length:  3.000 inches  Rotor Speed Rating In Rpm:  1725.0 single full load  Center To Center Distance Between Mounting Facilities Parallel To Width:  4.875 inches  Current Rating In Amps:  5.400 first multiple input or 10.800 second multiple input  Connection Type And Voltage Rating In Volts:  230.0 line to neutral first multiple input or 115.0 line to neutral second multiple input  Shaft End Characteristic:  A28 single style single end				

## NSN 6105-01-319-0129

Alternating Current Motor - Page 2 of 2



Frequency In Hertz:	Freq	uency	ln	Hertz:
---------------------	------	-------	----	--------

60.0 input

**Fsc Application Data:** 

Motors, electrical

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A271a0