

NSN 6105-01-319-0142 Alternating Current Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6105-01-319-0142 **Thread Class:** 3a single end **Thread Direction:** Right-hand single end **Overall Height:** 29.000 inches **Overall Length:** 46.300 inches **Overall Width:** 34.500 inches Thread Length: 1.250 inches single end **Undercut Diameter:** 1.125 inches single end **Shaft Diameter:** 1.1478 inches single end **Undercut Length:** 0.250 inches single end **Shaft Rotation Direction:** Clockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Open and dripproof protected-15 deg

Winding Type:

Induction-squirrel cage

Mounting Method:

Fixed base

Mounting Facility Type And Quantity:

4 unthreaded hole

Cooling Method:

Self-ventilated

Undercut Center To Shaft End Distance:

1.375 inches single end

Current Rating Method:

Load

Inclosure Specificationification:

Mil-std-108

Features Provided:

Horizontal mounting position

Frame Size Designation:

507ud

NSN 6105-01-319-0142Alternating Current Motor - Page 2 of 2



Power Rating:
250.000 horsepower output
Thread Size:
1.250 inches single end
Length Of Shaft From Housing:
3.750 inches single end
Shaft Center To Mounting Surface Distance:
12.444 inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length:
22.000 inches
Tempurature Rating:
50.0 ambient degrees celsius
Rotor Speed Rating In Rpm:
3570.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
20.000 inches
Current Rating In Amps:
285.000 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a28 second style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Thread Series Designator:
Unf single end
Terminal Type And Quantity:
3 solderless lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.