

View Online at <https://aerobasegroup.com/nsn/6105-01-325-1481>

Thread Class:

2b single end

Thread Direction:

Right-hand single end

Overall Height:

17.260 inches

Overall Length:

35.500 inches

Overall Width:

18.130 inches

Thread Length:

1.000 inches single end

Keyway Width:

0.380 inches single end

Keyway Depth:

0.190 inches single end

Shaft Diameter:

1.7490 inches single end and 1.7495 inches single end

Keyway Length:

2.750 inches single end

Shaft Rotation Direction:

Clockwise single end or counterclockwise single end

Duty Cycle:

Intermittent

Inclosure Feature:

Totally enclosed

Winding Type:

Induction-squirrel cage

Mounting Method:

Fixed base

Mounting Facility Type And Quantity:

4 unthreaded hole

Time Interval:

30.0 minutes off

Cooling Method:

Nonventilated

Current Rating Method:

Load

Inclosure Specificationification:

Mil-std-108

Features Provided:

Integral brake and horizontal mounting position

Frame Size Designation:

286tndz

Power Rating:

20.000 horsepower output

Thread Size:

0.500 inches single end

Length Of Shaft From Housing:

1.630 inches single end

Shaft Center To Mounting Surface Distance:

6.985 inches single end

Center To Center Distance Between Mounting Facilities Parallel To Length:

11.000 inches

Tempurature Rating:

50.0 ambient degrees celsius

Rotor Speed Rating In Rpm:

900.0 low full load and 1800.0 high full load

Center To Center Distance Between Mounting Facilities Parallel To Width:

11.000 inches

Current Rating In Amps:

25.000 low input or 30.000 high input

Connection Type And Voltage Rating In Volts:

440.0 line to neutral single input

Shaft End Characteristic:

A3 first style single end and a9 second style single end

Phase:

Three input

Frequency In Hertz:

60.0 input

Thread Series Designator:

Unc single end

Terminal Type And Quantity:

6 solderless lug

Fsc Application Data:

Slewing arm davit hoist

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.