Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-335-8328

Thread Class:

3a single end

**Overall Height:** 

10.440 inches

**Overall Length:** 

20.000 inches

**Overall Width:** 

14.080 inches

## Keyway Width:

0.188 inches single end

Keyway Depth:

0.188 inches single end

## Keyway Length:

1.218 inches single end

**Duty Cycle:** 

## Continuous

**Inclosure Feature:** 

Totally enclosed

Winding Type:

Induction-squirrel cage

Mounting Method:

Fixed base

Mounting Facility Type And Quantity:

4 unthreaded hole

**Cooling Method:** 

Nonventilated

**Current Rating Method:** 

Load

Inclosure Specificationification:

Mil-std-108

**Features Provided:** 

Horizontal mounting position

Frame Size Designation:

213tncz

**Power Rating:** 

5.000 horsepower output

Thread Size:

0.500 inches single end

Length Of Shaft From Housing:

6.250 inches single end

Shaft Center To Mounting Surface Distance:

5.235 inches single end

Alternating Current Motor - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To Length:
5.500 inches
Tempurature Rating:
50.0 ambient degrees celsius
Rotor Speed Rating In Rpm:
3545.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
8.500 inches
Current Rating In Amps:
7.000 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Phase:
Three input
Frequency In Hertz:
60.0 input
Thread Series Designator:
Unc single end
Terminal Type And Quantity:
3 wire lead
Fsc Application Data:
Pump trans distance wtr
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.