## NSN 6105-01-336-6048

Overall Length: 24.120 inches

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-336-6048

| Overall Width:   |
|--|
| 14.000 inches  |
| Thread Length:   |
| 0.660 inches single end  |
| Keyway Width:  |
| 0.376 inches single end  |
| Keyway Depth:  |
| 0.209 inches single end  |
| Shaft Diameter:  |
| 1.6245 inches single end   |
| Keyway Length:   |
| 3.000 inches single end  |
| Duty Cycle:  |
| Continuous   |
| Inclosure Feature:   |
| Spray tight  |
| Winding Type:  |
| Induction-squirrel cage  |
| Mounting Method:   |
| Face   |
|  |
| Mounting Facility Type And Quantity:   |
| Mounting Facility Type And Quantity: 4 threaded hole   |
|  |
| 4 threaded hole  |
| 4 threaded hole  Cooling Method:   |
| 4 threaded hole  Cooling Method:  Nonventilated  |
| 4 threaded hole  Cooling Method:  Nonventilated  Current Rating Method:  |
| 4 threaded hole  Cooling Method:  Nonventilated  Current Rating Method:  Load  |
| 4 threaded hole  Cooling Method:  Nonventilated  Current Rating Method:  Load  Inclosure Specificationification:   |
| 4 threaded hole  Cooling Method:  Nonventilated  Current Rating Method:  Load  Inclosure Specificationification:  Mil-std-108  |
| 4 threaded hole  Cooling Method: Nonventilated  Current Rating Method: Load Inclosure Specificationification: Mil-std-108  Features Provided:  |
| 4 threaded hole  Cooling Method: Nonventilated  Current Rating Method: Load Inclosure Specificationification: Mil-std-108  Features Provided: Vertical mounting position and horizontal mounting position  |
| 4 threaded hole  Cooling Method: Nonventilated  Current Rating Method: Load Inclosure Specificationification: Mil-std-108  Features Provided: Vertical mounting position and horizontal mounting position  Frame Size Designation:   |
| 4 threaded hole  Cooling Method: Nonventilated  Current Rating Method: Load Inclosure Specificationification: Mil-std-108  Features Provided: Vertical mounting position and horizontal mounting position  Frame Size Designation: 256tncz   |
| 4 threaded hole  Cooling Method: Nonventilated  Current Rating Method: Load Inclosure Specificationification: Mil-std-108  Features Provided: Vertical mounting position and horizontal mounting position  Frame Size Designation: 256tncz  Power Rating:  |
| 4 threaded hole  Cooling Method: Nonventilated  Current Rating Method: Load Inclosure Specificationification: Mil-std-108  Features Provided: Vertical mounting position and horizontal mounting position  Frame Size Designation: 256tncz  Power Rating: 7.500 horsepower output  |
| 4 threaded hole  Cooling Method: Nonventilated  Current Rating Method: Load Inclosure Specificationification: Mil-std-108  Features Provided: Vertical mounting position and horizontal mounting position  Frame Size Designation: 256tncz  Power Rating: 7.500 horsepower output  Length Of Shaft From Housing:   |
| 4 threaded hole  Cooling Method: Nonventilated  Current Rating Method: Load Inclosure Specificationification: Mil-std-108  Features Provided: Vertical mounting position and horizontal mounting position Frame Size Designation: 256tncz  Power Rating: 7.500 horsepower output Length Of Shaft From Housing: 4.930 inches single end                     |
| 4 threaded hole  Cooling Method: Nonventilated  Current Rating Method: Load Inclosure Specificationification: Mil-std-108  Features Provided: Vertical mounting position and horizontal mounting position Frame Size Designation: 256tncz  Power Rating: 7.500 horsepower output Length Of Shaft From Housing: 4.930 inches single end Tempurature Rating: |

## NSN 6105-01-336-6048

Alternating Current Motor - Page 2 of 2



## **Rotor Speed Rating In Rpm:** 1180.0 low full load and 1775.0 high full load **Current Rating In Amps:** 4.400 low input or 9.900 high input **Connection Type And Voltage Rating In Volts:** 440.0 line to neutral single input **Shaft End Characteristic:** A2 first style single end and a9 second style single end Phase: Three input **Special Features:** Threaded end-1.563-18 usf Frequency In Hertz: 60.0 input **Terminal Type And Quantity:** 6 solderless lug **Fsc Application Data:** Vnxl fan Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A271a0

Mil-std-108 spec.

Mil-std (military Standard):