NSN 6105-01-339-7988

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-339-7988 **Thread Class:** 3a single end **Thread Direction:** Right-hand single end **Overall Height:** 19.060 inches **Overall Length:** 32.750 inches **Overall Width:** 16.000 inches Thread Length: 1.000 inches single end **Shaft Diameter:** 0.625 inches single end **Shaft Rotation Direction:** Counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Totally enclosed Winding Type: Induction-squirrel cage **Mounting Method:** Fixed base **Mounting Facility Type And Quantity:** 4 unthreaded hole **Cooling Method:** Fan cooled **Current Rating Method:** Load **Inclosure Specificationification:** Mil-std-108 **Features Provided:** Horizontal mounting position Frame Size Designation: 326 **Power Rating:** 40.000 horsepower output **Thread Size:** 0.625 inches single end

Length Of Shaft From Housing: 8.380 inches single end

NSN 6105-01-339-7988Alternating Current Motor - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To Length:
12.000 inches
Tempurature Rating:
50.0 ambient degrees celsius
Mounting Facility Circle Diameter:
0.940 inches
Rotor Speed Rating In Rpm:
3555.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
12.500 inches
Current Rating In Amps:
45.500 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 single style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Thread Series Designator:
Unc single end
Terminal Type And Quantity:
3 solderless lug
Fsc Application Data:
Motors, electrical
Reference Number Differentiating Characteristics:
Magnetic permeability shall not exceed 2.0 after fabrication
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.