NSN 6105-01-360-8792

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-360-8792

Overall Length:
20.781 inches
Overall Width:
11.750 inches
Keyway Width:
0.250 inches single end
Keyway Depth:
0.250 inches single end
Shaft Diameter:
1.3745 inches single end and 1.3750 inches single end
Keyway Length:
3.000 inches single end
Duty Cycle:
Continuous
Inclosure Feature:
Dripproof-15 deg
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
4 unthreaded hole
Frame Size Designation:
254a
2544
Power Rating:
Power Rating:
Power Rating: 10.000 horsepower output
Power Rating: 10.000 horsepower output Length Of Shaft From Housing:
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating:
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius Mounting Facility Circle Diameter:
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius Mounting Facility Circle Diameter: 0.188 inches
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius Mounting Facility Circle Diameter: 0.188 inches Rotor Speed Rating In Rpm:
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius Mounting Facility Circle Diameter: 0.188 inches Rotor Speed Rating In Rpm: 1725.0 single full load
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius Mounting Facility Circle Diameter: 0.188 inches Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width:
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius Mounting Facility Circle Diameter: 0.188 inches Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 9.000 inches
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius Mounting Facility Circle Diameter: 0.188 inches Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 9.000 inches Current Rating In Amps:
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius Mounting Facility Circle Diameter: 0.188 inches Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 9.000 inches Current Rating In Amps: 73.000 single input
Power Rating: 10.000 horsepower output Length Of Shaft From Housing: 3.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius Mounting Facility Circle Diameter: 0.188 inches Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 9.000 inches Current Rating In Amps: 73.000 single input Connection Type And Voltage Rating In Volts:

NSN 6105-01-360-8792

Direct Current Motor - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0