NSN 6105-01-362-3026

1.380 inches first end1.260 inches second end

2.374 inches first end2.124 inches second end

Thread Class:

Overall Length: 44.690 inches Overall Width: 28.380 inches Thread Length:

Shaft Diameter:

Duty Cycle:

2a first end2a second end

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-362-3026

Inclosure Feature: Watertight Winding Type: Induction-squirrel cage Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Thready Qty Per Inch (tpi): 8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.000 inches	Intermittent
Winding Type: Induction-squirrel cage Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Thready Qty Per Inch (tpi): 8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Inclosure Feature:
Induction-squirrel cage Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Thready Qty Per Inch (tpi): 8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Watertight
Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Thready Qty Per Inch (tpi): 8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Winding Type:
Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Thready Qty Per Inch (tpi): 8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Induction-squirrel cage
Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Thready Qty Per Inch (tpi): 8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Mounting Method:
4 unthreaded hole Current Rating Method: Load Thready Qty Per Inch (tpi): 8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Fixed base
Current Rating Method: Load Thready Qty Per Inch (tpi): 8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Mounting Facility Type And Quantity:
Thready Qty Per Inch (tpi): 8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	4 unthreaded hole
Thready Qty Per Inch (tpi): 8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Current Rating Method:
8 first end8 second end Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Load
Frame Size Designation: 405 Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Thready Qty Per Inch (tpi):
Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	8 first end8 second end
Power Rating: 25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Frame Size Designation:
25.000 horsepower output Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	405
Thread Size: 1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Power Rating:
1.750 inches first end1.500 inches second end Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	25.000 horsepower output
Length Of Shaft From Housing: 6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Thread Size:
6.440 inches first end4.380 inches second end Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	1.750 inches first end1.500 inches second end
Shaft Center To Mounting Surface Distance: 9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Length Of Shaft From Housing:
9.700 inches first end9.700 inches second end Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	6.440 inches first end4.380 inches second end
Center To Center Distance Between Mounting Facilities Parallel To Length: 13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Shaft Center To Mounting Surface Distance:
13.750 inches Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	9.700 inches first end9.700 inches second end
Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Center To Center Distance Between Mounting Facilities Parallel To Length:
50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	13.750 inches
Rotor Speed Rating In Rpm: 1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	Tempurature Rating:
1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load Center To Center Distance Between Mounting Facilities Parallel To Width:	50.0 ambient degrees celsius
Center To Center Distance Between Mounting Facilities Parallel To Width:	Rotor Speed Rating In Rpm:
	1675.0 first multiple full load and 775.0 second multiple full load and 350.0 third multiple full load
16.000 inches	Center To Center Distance Between Mounting Facilities Parallel To Width:
	16.000 inches

NSN 6105-01-362-3026

Alternating Current Motor - Page 2 of 2



Current Rating In Amps:

34.000 first multiple input or 38.000 second multiple input or 34.000 third multiple input

Connection Type And Voltage Rating In Volts:

440.0 line to neutral single input

Shaft End Characteristic:

A2 first style first end and a3 second style first end and a9 third style first enda2 first style second end and a3 second style second end and a9 third style second end

_				
D	h٠	30	Δ.	•

Three input

Frequency In Hertz:

60.0 input

Thread Series Designator:

Un first endun second end

Terminal Type And Quantity:

3 solderless lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0