Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-366-2106

Thread Class:

3a single end

**Thread Direction:** 

Right-hand single end

## **Overall Height:**

32.250 inches

#### **Overall Length:**

42.125 inches

#### **Overall Width:**

31.812 inches

#### **Thread Length:**

0.625 inches single end

#### Taper Length:

1.500 inches single end

#### Keyway Width:

0.501 inches single end

## Keyway Depth:

0.501 inches single end

#### Shaft Diameter:

2.000 inches single end

#### Keyway Length:

1.375 inches single end

### **Shaft Rotation Direction:**

Clockwise single end or counterclockwise single end

#### **Duty Cycle:**

Continuous

#### **Inclosure Feature:**

Dripproof-45 deg

#### Winding Type:

Induction-squirrel cage

#### **Mounting Method:**

Face

# Mounting Facility Type And Quantity:

16 unthreaded hole

## **Cooling Method:**

Fan cooled

## **Current Rating Method:**

Load

## Inclosure Specificationification:

Mil-std-108

## Features Provided:

Vertical mounting position

# **NSN 6105-01-366-2106** Alternating Current Motor - Page 2 of 2



Frame Size Designation:	
505wvy	
Power Rating:	
265.000 horsepower output	
Thread Size:	
1.375 inches single end	
Taper:	
0.750 per foot in inches single end	
Length Of Shaft From Housing:	
3.500 inches single end	
Tempurature Rating:	
50.0 ambient degrees celsius	
Mounting Facility Circle Diameter:	
22.000 inches	
Rotor Speed Rating In Rpm:	
3564.0 single full load	
Current Rating In Amps:	
295.000 single input	
Connection Type And Voltage Rating In Volts:	
440.0 line to neutral single input	
Shaft End Characteristic:	
A2 first style single end and a9 second style single end and a3 third s	tyle single end
Phase:	
Three input	
Frequency In Hertz:	
60.0 input	
Thread Series Designator:	
Unf single end	
Terminal Type And Quantity:	
6 solderless lug	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A271a0	
Mil-std (military Standard):	
Mil-std-108 spec.	