Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-377-6257

| Thread Class:                        |
|--------------------------------------|
| 3a first end                         |
| Overall Height:                      |
| 24.880 inches                        |
| Overall Length:                      |
| 46.900 inches                        |
| Thread Length:                       |
| 0.630 inches first end               |
| Keyway Width:                        |
| 0.500 inches second end              |
| Keyway Depth:                        |
| 0.500 inches first end               |
| Shaft Diameter:                      |
| 2.124 inches second end              |
| Keyway Length:                       |
| 3.000 inches first end               |
| Duty Cycle:                          |
| Continuous                           |
| Inclosure Feature:                   |
| Watertight                           |
| Winding Type:                        |
| Induction-squirrel cage              |
| Mounting Method:                     |
| Fixed base                           |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole                    |
| Cooling Method:                      |
| Fan cooled                           |
| Current Rating Method:               |
| Load                                 |
| Features Provided:                   |
| Vertical mounting position           |
| Thready Qty Per Inch (tpi):          |
| 8 second end                         |
| Frame Size Designation:              |
| 445tdz                               |
| Power Rating:                        |
| 75.000 horsepower output             |
| Thread Size:                         |
| 1.750 inches first end               |
| Length Of Shaft From Housing:        |
| 3.468 inches single end              |
|                                      |

## **NSN 6105-01-377-6257** Alternating Current Motor - Page 2 of 2



|         | Center To Mounting Surface Distance:                                 |
|---------|--|
|         | 0 inches single end  |
|         | er To Center Distance Between Mounting Facilities Parallel To Length |
|         | 0 inches   |
|         | urature Rating:  |
|         | ambient degrees celsius  |
|         | Speed Rating In Rpm:   |
|         | low full load and 1630.0 high full load                              |
|         | er To Center Distance Between Mounting Facilities Parallel To Width: |
|         | 0 inches   |
|         | nt Rating In Amps:   |
|         | 0 low input or 100.000 high input                                    |
|         | ection Type And Voltage Rating In Volts:                             |
|         | line to neutral single input   |
| Shaft   | End Characteristic:  |
| A2 firs | st style second end and a29 second style second end                  |
| Phase   | e:   |
| Three   | input  |
| Frequ   | iency In Hertz:  |
| 60.0 iı | nput   |
| Threa   | d Series Designator:   |
| Unf fir | st end   |
| Termi   | inal Type And Quantity:  |
| 4 wire  | lead   |
| Shelf   | Life:  |
| N/a     |  |
| Unit C  | Df Measure:  |
|         |  |
| Demil   | litarization:  |
| No      |  |
| Fiig:   |  |
| A271a   | a0   |