Alternating Current Motor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6105-01-387-4366

Nounting Method: Pedestal Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Fan cooled Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Concection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Tree input Frequency In Hertz: 60.0 input Sheft Life: Na Unit Of Measure: Duriel Terzetion:		
Duty Cycle: Continuous Inclosure Feature: Totally enclosed Mounting Method: Pedestal Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Fan cooled Current Rating Method: Ead Inclosure Specification/fication: Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1.320.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Votage Rating In Vots: 440.0 line to neutral single input Phase: Three input Fraeuency In Hertz: 60.0 input Shef Life: Na Unit Of Measure: Tempurature Italies Output Demiliterization:		
Inclosure Feature: Totally enclosed Mounting Method: Pedestal Mounting Scillty Type And Quantity: 4 unthreaded hole Cooling Method: Ean cooled Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: L162te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tompurature Rating: 5.0.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1.3200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shef Life: Na Unit Of Measure: Demilitarization:		
Inclosure Feature: Totally enclosed Tota		
Totally enclosed Mounting Method: Pedestal Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Fan cooled Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: L162te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 5.0.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Sheft Life: Na Unit Of Measure: Pre- During Intertized		
Nounting Method: Pedestal Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Fan cooled Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Concection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Tree input Frequency In Hertz: 60.0 input Sheft Life: Na Unit Of Measure: Duriel Terzetion:	Inclosure Feature:	
Pedestal Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Fan cooled Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Lagth Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 1.300 a mbient degrees celsius Rotor Spece Rating In Rpm: 1200.0 single full toad Current Rating In Amps: 1.740 single input Phase: Three input Frequecy In Hertz: 6.00 input Shaft I: Na Unit Of Measure: Current	Totally enclosed	
Mounting Facility Type And Quantity: 4 unthreaded hole Coling Method: Fan cooled Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Lagth Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 120.0 single full load Current Rating In Amps: 1.740 single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit of Measure: Phenilitarization:	Mounting Method:	
4 unthreaded hole Cooling Method: Fan cooled Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1.200.0 single full load Current Rating In Amps: 1.740 single input Concetion Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Sheft Life: N/a Dint of Measure:	Pedestal	
Coling Method: Fan cooled Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Length of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hetz: 6.0 input Shelf Life: Na Shelf Life: Na Dird Measure:	Mounting Facility Type And Quantity:	
Fan cooled Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Phase: Three input Frequency In Hertz: 60.0 input Sheft Life: N/a Unit Of Measure:	4 unthreaded hole	
Current Rating Method: Load Inclosure Specificationification: Nema Frame Size Designation: L1821e Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.000 horsepower output Length Of Shaft From Housing: 1.100 inches identical ends Tempurature Rating: 5.00 ambient degrees celsius Rotor Speed Rating In Rpm: 5.00 ambient degrees celsius Rotor Speed Rating In Rpm: 1.200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 40.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Sheff Life: N/a Din fof Measure: Demilitarization:	Cooling Method:	
Load Iclosure Specificationification: Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Fan cooled	
Inclosure Specificationification: Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Sheft Life: N/a Unit Of Measure: Demilitarization:	Current Rating Method:	
Nema Frame Size Designation: L182te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 3.00 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.00 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.00 line to neutral single input Phase: Three input Frequency In Hertz: 60.01 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Load	
Frame Size Designation: L182te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Inclosure Specificationification:	
L182te Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Nema	
Power Rating: 1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Frame Size Designation:	
1.000 horsepower output Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Sheff Life: N/a Unit Of Measure: Demilitarization:	L182te	
Length Of Shaft From Housing: 1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Sheff Life: N/a Unit Of Measure: Demilitarization:	Power Rating:	
1.310 inches identical ends Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	1.000 horsepower output	
Tempurature Rating: 50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Length Of Shaft From Housing:	
50.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	1.310 inches identical ends	
Rotor Speed Rating In Rpm: 1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: 	Tempurature Rating:	
1200.0 single full load Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	50.0 ambient degrees celsius	
Current Rating In Amps: 1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Rotor Speed Rating In Rpm:	
1.740 single input Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: 	1200.0 single full load	
Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: 	Current Rating In Amps:	
440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	1.740 single input	
Phase: Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Connection Type And Voltage Rating In Volts:	
Three input Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	440.0 line to neutral single input	
Frequency In Hertz: 60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Phase:	
60.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Three input	
Shelf Life: N/a Unit Of Measure: Demilitarization:	Frequency In Hertz:	
N/a Unit Of Measure: Demilitarization:	60.0 input	
Unit Of Measure: Demilitarization:	Shelf Life:	
 Demilitarization:	N/a	
Demilitarization:	Unit Of Measure:	
No	Demilitarization:	
	No	
Fiig:	Fiig:	
A271a0	A271a0	