Alternating Current Motor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6105-01-439-6010

| 0 | Duty Cycle:                                  |
|---|--|
| C | Continuous                                   |
| I | nclosure Feature:                            |
| ٦ | otally enclosed                              |
| ۷ | Vinding Type:                                |
| I | nduction-squirrel cage                       |
| C | Cooling Method:                              |
| F | an cooled                                    |
| C | Current Rating Method:                       |
| L | oad  |
| I | nclosure Specificationification:             |
| Ν | /iil-std-108                                 |
| F | rame Size Designation:                       |
| 2 | 54tcn  |
| F | Power Rating:                                |
| 1 | 0.000 horsepower output                      |
| F | Rotor Speed Rating In Rpm:                   |
| 3 | 600.0 single full load                       |
| C | Current Rating In Amps:                      |
| 1 | 1.800 single input                           |
| C | Connection Type And Voltage Rating In Volts: |
| 4 | 40.0 line to neutral single input            |
| F | Phase:                                       |
| ٦ | Three input                                  |
| F | requency In Hertz:                           |
| 6 | 0.0 input                                    |
| ŝ | Shelf Life:                                  |
| ١ | I/a  |
| ι | Init Of Measure:                             |
| - |  |
| 0 | Demilitarization:                            |
| ١ | lo   |
| F | iig:   |
| P | 271a0  |
| Ν | /il-std (military Standard):                 |
| Ν | /il-std-108 spec.                            |