NSN 6105-01-464-4388

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-464-4388

Overall Height:
448.5 millimeters
Overall Length:
834.0 millimeters
Overall Width:
364.0 millimeters
Shaft Diameter:
48.0 millimeters second end
End Application:
Hydraulic power unit; a-12660 rev. 0
Duty Cycle:
Continuous
Winding Type:
Induction-squirrel cage
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
Unthreaded hole
Cooling Method:
Ambient air
Keyway Center To Shaft End Distance:
Reyway Center 10 Chart Life Distance.
65.0 millimeters second end
65.0 millimeters second end
65.0 millimeters second end Length Of Shaft From Housing:
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance:
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter:
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters Rotor Speed Rating In Rpm:
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters Rotor Speed Rating In Rpm: 1752.0 single full load
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters Rotor Speed Rating In Rpm: 1752.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width:
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters Rotor Speed Rating In Rpm: 1752.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 279.0 millimeters
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters Rotor Speed Rating In Rpm: 1752.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 279.0 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height:
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters Rotor Speed Rating In Rpm: 1752.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 279.0 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 279.0 millimeters
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters Rotor Speed Rating In Rpm: 1752.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 279.0 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 279.0 millimeters Shaft End Characteristic:
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters Rotor Speed Rating In Rpm: 1752.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 279.0 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 279.0 millimeters Shaft End Characteristic: A11 second style second end
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters Rotor Speed Rating In Rpm: 1752.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 279.0 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 279.0 millimeters Shaft End Characteristic: A11 second style second end Product Name:
65.0 millimeters second end Length Of Shaft From Housing: 110.0 millimeters identical ends Shaft Center To Mounting Surface Distance: 180.0 millimeters first end Mounting Facility Circle Diameter: 15.0 millimeters Rotor Speed Rating In Rpm: 1752.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 279.0 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 279.0 millimeters Shaft End Characteristic: A11 second style second end Product Name: Electric drive motor

60.0 input

NSN 6105-01-464-4388

Alternating Current Motor - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0