NSN 6110-00-238-6016

Voltage Regulator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6110-00-238-6016

Overall Length:
2.250 inches
Overall Height:
2.000 inches
Overall Width:
2.250 inches
Mounting Hole Diameter:
0.164 inches
Center To Center Distance Between Mounting Holes:
0.438 inches
Mounting Hole Quantity:
2
Mounting Method:
Threaded hole or unthreaded hole
End Application:
Type no. Gn-58
Regulation Method:
Electromechanical
Compensation Provided:
Differential cross current
Regulation Percent:
8.000
8.000 Input Current Type:
Input Current Type:
Input Current Type: Ac and dc
Input Current Type: Ac and dc Input Voltage Rating In Volts:
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating:
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts Inclosure Feature:
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts Inclosure Feature: Closed frame
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts Inclosure Feature: Closed frame Special Features:
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts Inclosure Feature: Closed frame Special Features: Moisture and fungus resistant
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts Inclosure Feature: Closed frame Special Features: Moisture and fungus resistant Shelf Life:
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts Inclosure Feature: Closed frame Special Features: Moisture and fungus resistant Shelf Life: N/a
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts Inclosure Feature: Closed frame Special Features: Moisture and fungus resistant Shelf Life: N/a
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts Inclosure Feature: Closed frame Special Features: Moisture and fungus resistant Shelf Life: N/a Unit Of Measure:
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts Inclosure Feature: Closed frame Special Features: Moisture and fungus resistant Shelf Life: N/a Unit Of Measure: Demilitarization:
Input Current Type: Ac and dc Input Voltage Rating In Volts: 425.0 and 105.0 and 6.3 and 1.4 Power Rating: 48.800 watts and 3.700 watts and 15.400 watts and 0.600 watts Inclosure Feature: Closed frame Special Features: Moisture and fungus resistant Shelf Life: N/a Unit Of Measure: Demilitarization: No