## NSN 6110-00-242-4065

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-00-242-4065

| Speed Adjustments:   |
|--|
| Single speed   |
| Overall Length:  |
| 20.562 inches  |
| Overall Height:  |
| 10.312 inches  |
| Overall Width:   |
| 15.000 inches  |
| Actuation Method:  |
| Magnetic   |
| Performance Type:  |
| Semiautomatic  |
| Fuse Accommodation Quantity:   |
| 1  |
| Duty Cycle:  |
| Continuous   |
| Mounting Configuration:  |
| Four 7/16 in. Diameter mtg holes on 18-3/8 in. By 10-1/2 in. Mtg centers |
| Operating Voltage Characteristic:  |
| Reduced  |
| Voltage Reduction Method:  |
| Resistor   |
| Full Voltage Restoring Method:   |
| Current limit acceleration   |
| Horsepower Rating:   |
| 7.600 and 10.000   |
| Actuator Voltage:  |
| 230.0 dc   |
| Load Protection Type:  |
| Overload or undervoltage   |
| Ambient Temp:  |
| 50.0 degrees celsius   |
| Inclosure Feature:   |
| Dripproof  |
| Switch Functional Positions:   |
| Start and stop   |
| Control Type:  |
| Local  |
| Features Provided:   |
| Circuit protection fuse  |
| Specification Or Standard:   |

3 size

## **NSN 6110-00-242-4065** Motor Starter - Page 2 of 2

A541c0



| Reference Number Differentiating Characteristics: |
|---|
| Acut ancy   |
| Shelf Life:                                       |
| N/a   |
| Unit Of Measure:                                  |
|   |
| Demilitarization:                                 |
| No  |
| Fiig:   |