NSN 6110-00-468-2337

Motor Starter - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/6110-00-468-2337

| Speed Adjustments: | | | | | | |
|---|--|--|--|--|--|--|
| Single speed | | | | | | |
| Overall Length: | | | | | | |
| 15.500 inches | | | | | | |
| Overall Height: | | | | | | |
| 20.000 inches | | | | | | |
| Overall Width: | | | | | | |
| 15.594 inches | | | | | | |
| Unable To Decode: | | | | | | |
| Unable to decode and unable to decode | | | | | | |
| Actuation Method: | | | | | | |
| Magnetic | | | | | | |
| Performance Type: | | | | | | |
| Semiautomatic | | | | | | |
| Fuse Accommodation Quantity: | | | | | | |
| 2 | | | | | | |
| Duty Cycle: | | | | | | |
| Continuous | | | | | | |
| Mounting Configuration: | | | | | | |
| Six 21/32 in. Diameter mtg holes in 2 rows, 3 holes in ea row spaced 5-1/2 in. C to c rowsspaced 17-5/8 in. Apart | | | | | | |
| Operating Voltage Characteristic: | | | | | | |
| Reduced | | | | | | |
| Voltage Reduction Method: | | | | | | |
| Resistor | | | | | | |
| Full Voltage Restoring Method: | | | | | | |
| Current limit acceleration | | | | | | |
| Horsepower Rating: | | | | | | |
| 15.000 | | | | | | |
| Actuator Voltage: | | | | | | |
| 250.0 dc | | | | | | |
| Load Protection Type: | | | | | | |
| Undervoltage release | | | | | | |
| Ambient Temp: | | | | | | |
| 40.0 degrees celsius | | | | | | |
| Inclosure Feature: | | | | | | |
| Dripproof | | | | | | |
| Control Type: | | | | | | |
| Remote | | | | | | |
| Features Provided: | | | | | | |
| Circuit protection fuse | | | | | | |
| Shelf Life: | | | | | | |

NSN 6110-00-468-2337

Motor Starter - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A541c0