NSN 6110-00-624-1901

Magnetic Contactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-00-624-1901

| lazardous Locations/environmental Protection: | |
|---|--|
| Dripproof | |
| Overall Length: | |
| 5.600 inches | |
| Overall Height: | |
| 5.160 inches | |
| Overall Width: | |
| 5.400 inches | |
| Ac Voltage Rating: | |
| 15.0 volts | |
| Actuation Method: | |
| /lagnetic | |
| Performance Type: | |
| Semiautomatic | |
| Duty Cycle: | |
| Continuous | |
| Nounting Configuration: | |
| Four 7/32 in. Diameter mtg holes on 4 in. By 4 in. Mtg ctr | |
| Operating Voltage Characteristic: | |
| Full | |
| lorsepower Rating: | |
| 2.000 | |
| Ambient Temp: | |
| i0.0 degrees celsius | |
| nclosure Feature: | |
| Dpen | |
| National Electrical Manufacturers Association Standards Design: | |
| Designed per nema std | |
| Amp Size Rating: | |
| 8.0 | |
| Switch Functional Positions: | |
| Start and stop | |
| Control Type: | |
| Local | |
| Features Provided: | |
| Accessory location internal | |
| Shelf Life: | |
| J/a | |
| Jnit Of Measure: | |
| - | |
| Demilitarization: | |
| | |
| | |

NSN 6110-00-624-1901 Magnetic Contactor - Page 2 of 2

Fiig: A541d0

