NSN 6110-00-713-4176

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-00-713-4176

Speed Adjustments:
Single speed
Overall Length:
6.500 inches
Overall Height:
3.500 inches
Overall Width:
3.500 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Semiautomatic
Duty Cycle:
Continuous
Mounting Configuration:
Three 0.190 in. Diameter holes spaced on the corners of an isoceles triangle base 3.500 in., altitude 5.000 in.
Operating Voltage Characteristic:
Full
Horsepower Rating:
10.000
Actuator Voltage:
115.0 ac
Load Protection Type:
Loud Followin Type.
Overload and undervoltage
Overload and undervoltage
Overload and undervoltage Ambient Temp:
Overload and undervoltage Ambient Temp: 70.0 degrees celsius
Overload and undervoltage Ambient Temp: 70.0 degrees celsius Inclosure Feature:
Overload and undervoltage Ambient Temp: 70.0 degrees celsius Inclosure Feature: Dripproof
Overload and undervoltage Ambient Temp: 70.0 degrees celsius Inclosure Feature: Dripproof Control Type:
Overload and undervoltage Ambient Temp: 70.0 degrees celsius Inclosure Feature: Dripproof Control Type: Remote
Overload and undervoltage Ambient Temp: 70.0 degrees celsius Inclosure Feature: Dripproof Control Type: Remote Phase:
Overload and undervoltage Ambient Temp: 70.0 degrees celsius Inclosure Feature: Dripproof Control Type: Remote Phase: Three
Overload and undervoltage Ambient Temp: 70.0 degrees celsius Inclosure Feature: Dripproof Control Type: Remote Phase: Three Frequency In Hertz:
Overload and undervoltage Ambient Temp: 70.0 degrees celsius Inclosure Feature: Dripproof Control Type: Remote Phase: Three Frequency In Hertz: 60.0

--

NSN 6110-00-713-4176

Motor Starter - Page 2 of 2



Demilitarization:

No

Fiig:

A541c0