NSN 6110-00-811-3423

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-00-811-3423

Overall Length:
4.500 inches
Overall Height:
4.000 inches
Overall Width:
5.125 inches
Ac Voltage Rating:
600.0 volts
Frequency Rating:
50.0 hertz
Actuation Method:
Magnetic
Performance Type:
Semiautomatic
Size Designator:
0
Duty Cycle:
Continuous
Mounting Configuration:
Three 0.250 in. Screws slots spaced irregularly
Operating Voltage Characteristic:
Full
Horsepower Rating:
5.000
Actuator Voltage:
Actuator Voltage: 380.0 ac
380.0 ac
380.0 ac Load Protection Type:
380.0 ac Load Protection Type: Overload or undervoltage
380.0 ac Load Protection Type: Overload or undervoltage Ambient Temp:
380.0 ac Load Protection Type: Overload or undervoltage Ambient Temp: 65.0 degrees celsius
380.0 ac Load Protection Type: Overload or undervoltage Ambient Temp: 65.0 degrees celsius Inclosure Feature:
380.0 ac Load Protection Type: Overload or undervoltage Ambient Temp: 65.0 degrees celsius Inclosure Feature: Open
380.0 ac Load Protection Type: Overload or undervoltage Ambient Temp: 65.0 degrees celsius Inclosure Feature: Open National Electrical Manufacturers Association Standards Design:
380.0 ac Load Protection Type: Overload or undervoltage Ambient Temp: 65.0 degrees celsius Inclosure Feature: Open National Electrical Manufacturers Association Standards Design: Designed per nema std
380.0 ac Load Protection Type: Overload or undervoltage Ambient Temp: 65.0 degrees celsius Inclosure Feature: Open National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type:
380.0 ac Load Protection Type: Overload or undervoltage Ambient Temp: 65.0 degrees celsius Inclosure Feature: Open National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Remote
Load Protection Type: Overload or undervoltage Ambient Temp: 65.0 degrees celsius Inclosure Feature: Open National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Remote Phase:
Load Protection Type: Overload or undervoltage Ambient Temp: 65.0 degrees celsius Inclosure Feature: Open National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Remote Phase: Three
Load Protection Type: Overload or undervoltage Ambient Temp: 65.0 degrees celsius Inclosure Feature: Open National Electrical Manufacturers Association Standards Design: Designed per nema std Control Type: Remote Phase: Three Frequency In Hertz:

NSN 6110-00-811-3423

Motor Starter - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A541c0