NSN 6110-00-829-1052

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-00-829-1052

Speed Adjustments:
Single speed
Overall Length:
10.375 inches
Overall Height:
5.688 inches
Overall Width:
8.375 inches
Ac Voltage Rating:
110.0 volts
Frequency Rating:
50.0 hertz
Actuation Method:
Magnetic
Performance Type:
Automatic
Duty Cycle:
Continuous
Mounting Configuration:
Four mtg slots for 5/16 in. Bolts on 9-1/2 in. By 6 in. Centers
Operating Voltage Characteristic:
Operating Voltage Characteristic: Full
Full
Full Horsepower Rating:
Full Horsepower Rating: 3.000
Full Horsepower Rating: 3.000 Actuator Voltage:
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type:
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type: Overload and undervoltage
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type: Overload and undervoltage Inclosure Feature:
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type: Overload and undervoltage Inclosure Feature: Explosion proof
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type: Overload and undervoltage Inclosure Feature: Explosion proof Control Type:
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type: Overload and undervoltage Inclosure Feature: Explosion proof Control Type: Remote
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type: Overload and undervoltage Inclosure Feature: Explosion proof Control Type: Remote Phase:
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type: Overload and undervoltage Inclosure Feature: Explosion proof Control Type: Remote Phase: Three
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type: Overload and undervoltage Inclosure Feature: Explosion proof Control Type: Remote Phase: Three Frequency In Hertz:
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type: Overload and undervoltage Inclosure Feature: Explosion proof Control Type: Remote Phase: Three Frequency In Hertz: 50.0
Full Horsepower Rating: 3.000 Actuator Voltage: 110.0 ac Load Protection Type: Overload and undervoltage Inclosure Feature: Explosion proof Control Type: Remote Phase: Three Frequency In Hertz: 50.0 Shelf Life:

No

Demilitarization:

NSN 6110-00-829-1052

Motor Starter - Page 2 of 2



Fiig:

A541c0