NSN 6110-00-899-0059

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-00-899-0059

| Hazardous Locations/environmental Protection: |
|--|
| Dripproof |
| Overall Length: |
| 8.250 inches |
| Overall Height: |
| 15.875 inches |
| Overall Width: |
| 6.500 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Performance Type: |
| Semiautomatic |
| Fuse Accommodation Quantity: |
| 1 |
| Size Designator: |
| 1 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Four 17/32 in. Diameter mtg holes on 13-5/8 in. By 4-3/4 in. Mtg centers |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 5.000 |
| Actuator Voltage: |
| 220.0 ac |
| Fuse Current Rating In Amps: |
| 10.0 |
| Load Protection Type: |
| Overload and undervoltage |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Control Type: |

Remote

NSN 6110-00-899-0059

Motor Starter - Page 2 of 2



Circuit protection fuse

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541c0