Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-00-932-4604

Hazarous Locations/environmental Protection: Fungus resistant Overall Longth: 6.000 inches Overall Height: 3.875 inches Overall Width: 3.875 inches A voltage Rating: 3.875 inches A voltage Rating: 120.0 volts Frequery Rating: 120.0 volts 120.0 v		
Norrall Length:6.000 inchesOverall Height:3.875 inchesOverall Width:S.000 inchesAc Vottage Rating:1200 voltsFrequency Rating:1200 voltsFrequency Rating:Between 50.0 hertz and 60.0 hertzActuation Method:MagneticCatuation Method:Overall Application:Overall Application:Overall Catuation Quantity:Stez Designator:Overall Catuation Quantity:Stez Designator:Overall Catuation Method:Notice Catuation Quantity:Overall Catuation Quantity:Catuation Catuation:Overall Catuation:Overall Catuation:Overall Catuation:Overall Catuation:Overall Catuation:Overall Catuation:Overall Catuation:Overall Voltage Characteristic:Catuator Voltage:10.0 acCatuator Voltage:10.0 acCatuator Voltage:10.0 acCatuator Voltage:10.0 acCatuator Feature:Partially enclosedNational Electrical Manufacturers Association Standards Design:Partially enclosedAmostage Area astoAmostage Area astoAmos	Hazardous Locations/environmental Protection:	
Actool inches Overall Height: 3.875 inches Overall Width: 5.000 inches Ac Votage Rating: 120.0 volts Frequency Rating: 120.0 volts Frequency Rating: Between 50.0 hertz and 60.0 hertz Actuation Method: Magnetic End Application: Oav483/fpn44, 45 Performance Type: Manual Fuse Accommodation Quantity: 2 Size Designator: 0 Duty Cycle: Intermittent Operating Voltage Characteristic: Full Full Voltage Restoring Method: Counter enf acceleration Actuator Voltage: 10.0 ac Fuse Current Rating In Amps: 20.0 Ladd Protection Type: Overload Inclosure Feature: Parially enclosed National Electrical Manufacturers Association Standards Design: Paidally enclosed Amplize Rating: Paidally enclosed	Fungus resistant	
Overall Heigh:3.875 inchesOverall Width:5.00 inchesAc Voltage Rating:120.0 voltsFrequercy Rating:Between 60.0 hertz and 60.0 hertzActuation Method:MagneticEnd Application:Ox4483/fpn44, 45Performance Type:ManualFuse Accommodation Quantity:2Size Designator:0Operating Voltage Characteristic:FullPull Voltage Restoring Method:Youther emf accelerationActuator Voltage:10.0 acFuse Accorrent Asing In Amps:20.0Courter emf accelerationActuator Voltage:10.0 acFuse Accorrent Asing In Amps:20.0Corrent Stating In Amps:20.1Data Descriptic:Partially enclosedNational Electrical Manufacturers Association Standards Design:Partially enclosedAtoma Electrical Annufacturers Association Standards Design:18.0Chotrol Type:18.0Chotrol Type:18.0Control Type:Partially enclosedAtoma Electrical Annufacturers Association Standards Design:20.120.220.220.320.420.420.520.720.720.720.720.720.720.720.720.720.720.7 </td <td>Overall Length:</td> <td></td>	Overall Length:	
3475 inches Overall Width: 5.000 inches Ac Voltage Rating: 120.0 volts Frequency Rating: Between 50.0 hertz and 60.0 hertz Actuation Method: Magnetic End Application: Oar4433/fpn44, 45 Performance Type: Manual Fuse Accommodation Quantity: 2 Size Designator: 0 Operating Voltage Characteristic: Full Voltage Restoring Method: Counter emf acceleration Actuatior Voltage: 10.0 Counter emf acceleration Actuator Voltage: 10.0 Counter emf acceleration Actuator Voltage: 10.0 Counter emf acceleration Actuator Voltage: 10.0 Euse Current Rating In Amps: 2.0 Coderotection Type: Overload Inclosure Feature: Partial venclosed Actional Electrical Manufacturers Association Standards Design: Designed	6.000 inches	
Overall Width:5.000 inchesAc Voltage Rating:120.0 voltsFrequency Rating:Between 50.0 hertz and 60.0 hertzActuation Method:MagneticBetween 50.0 hertz and 60.0 hertzActuation Method:Outstream 50.0 hertz and 60.0 hertzManualFuse Accommodation Quantity:2Se Designator:00Duty Cycle:IntermittentOperating Voltage Characteristic:FullFullVoltage Restoring Method:Counter enf accelerationActuator Voltage:10.0 acFuse Current Rating In Amps:20.0LogandInclosedMational Electrical Monafacturers Association Standards Design:Designed per nema stdAmp Size Rating:18.018.0Contor Type:18.0Partially enclosedPartially enclosedAtoma Electrical Monafacturers Association Standards Design:Designed per nema stdAmp Size Rating:18.0Contor Type:19.019.019.019	Overall Height:	
S000 inchesAc Voltage Rating:120.0 voltsFrequency Rating:Between 50.0 hertz and 60.0 hertzActuation Method:MagneticEnd Application:Oad483/fpn44, 45Performance Type:ManualFuse Accommodation Quantity:2Size Designator:0Outrolly Cycle:IntermittentOperating Voltage Characteristic:FullFull Voltage Restoring Method:Counter enf accelerationActuator Voltage:10.0 acFull Counter Rating In Amps:20.0Load Protection Type:OreidadInclosure Feature:20.0Load Protection Type:20.1Stard Protection Type:20.2Stard Protection Type:20.3And Protection Type:20.420.520.620.7	3.875 inches	
Ac Voltage Rating: 120.0 volts Frequency Rating: Between 50.0 hertz and 60.0 hertz Actuation Method: Magnetic End Application: Oad483/fpn44, 45 Performance Type: Manual Fuse Accommodation Quantity: 2 Size Designator: 0 Duty Cycle: Intermittent Operating Voltage Characteristic: Full Full Voltage Restoring Method: Counter enf acceleration Actuator Voltage: 110.0 ac Fuse Accurent Rating In Amps: 2.0.0 Localer Feature: Portad Inclosure Feature: 12.0.0 Enderstorie In Amps: 2.0.0 Localer Potection Type: Overlad Inclosure Feature: Paritally enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0	Overall Width:	
120.0 volts Frequency Rating: Between 50.0 hertz and 60.0 hertz Actuation Method: Magnetic End Application: Oa4483/fpn44, 45 Performance Type: Manual Fuse Accommodation Quantity: 2 Size Designator: 0 Duty Cycle: Intermittent Operating Voltage Characteristic: Full Full Voltage Restoring Method: Counter enf acceleration Actuator Voltage: 110.0 ac Fuse Current Rating In Amps: 20.0 Laclorer Feature: Partially enclosed Neuroid Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Kutor Type:	5.000 inches	
Frequency Rating: Between 50.0 hertz and 60.0 hertz Actuation Method: Magnetic End Application: Oad483/fpn44, 45 Performance Type: Manual Fuse Accommodation Quantity: 2 Stace Designator: 0 Duty Cycle: Intermittent Operating Voltage Characteristic: Full Full Voltage Restoring Method: Counter emf acceleration Actuator Voltage: 10.0 ac Fuse Current Rating In Amps: 20.0 Lace Interview Feature: Parially enclosed Neurone Testing In Amps: 20.0 Lace Interview Feature: Parially enclosed National Electrical Manufacturers Association Standards Design: 18.0 Contor Type:	Ac Voltage Rating:	
Between 50.0 hertz and 60.0 hertz Actuation Method: Magnetic End Application: Oa4483/fpn44, 45 Performance Type: Manual Fuse Accommodation Quantity: 2 Size Designator: 0 Duty Cycle: Intermittent Operating Voltage Characteristic: Fuil Full Voltage Restoring Method: Courter emf acceleration Actuator Voltage: 10.0 ac Fuse Current Rating In Amps: 20.0 Local Protection Type: Overload Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0	120.0 volts	
Actuation Method:MagneticEnd Application:Oa4483/fpn44, 45Performance Type:ManualFuse Accommodation Quantity:2Size Designator:0Duty Cycle:IntermittentOperating Voltage Characteristic:FullFullCounter emf accelerationActuator Voltage:110.0 acFuse Current Rating In Amps:20.0CoverloadIndowre Feature:Portially enclosedActuator Step Feature:Partially enclosedActional Electrical Manufacturers Association Standards Design:Paste Rating:18.0Control Type:18.0Control Type:Paste Rating:18.0Control Type:Paste Rating:Paste Paste Paste Paste P	Frequency Rating:	
MagneticEnd Application:Oad483/fpn44, 45Performance Type:ManualFuse Accommodation Quantity:2Size Designator:0Duty Cycle:IntermittentOperating Voltage Characteristic:FullFullFull Voltage Restoring Method:Counter enf accelerationActuator Voltage:110.0 acFuse Current Rating In Amps:20.0Load Protection Type:OverloadInclosure Feature:Partially enclosedActuator Locating In Amps:20.0Load Protection Type:20.1Bardially enclosedActional Electrical Manufacturers Association Standards Design:20.2Designed per nema stdAmp Size Rating:18.0Control Type:20.1	Between 50.0 hertz and 60.0 hertz	
End Application:Qa4483/fpn44, 45Performance Type:ManualFuse Accommodation Quantity:2Size Designator:0Duty Cycle:IntermittentOperating Voltage Characteristic:FullFull Voltage Restoring Method:Counter emf accelerationActuator Voltage:10.0 acFuse Current Rating In Amps:20.0Load Protection Type:20.0Load Protection Type:QuericalIntensite Externet Rating In Amps:20.0Load Protection Type:QuericalInclosure Feature:Partially enclosedMational Electrical Manufacturers Association Standards Design:Designed per nema stdAmp Size Rating:18.0Control Type:	Actuation Method:	
Outed addition of the set of the se	Magnetic	
Performance Type:ManualFuse Accommodation Quantity:2Size Designator:0Duty Cycle:IntermittentOperating Voltage Characteristic:FullFullVoltage Restoring Method:Counter emf accelerationActuator Voltage:110.0 acFuse Current Rating In Amps:20.0Lodd Protection Type:OverloadInclosure Feature:Partially enclosedMational Electrical Manufacturers Association Standards Design:Designed per nema stdAmp Size Rating:18.0Contor Type:	End Application:	
Manual Fuse Accommodation Quantity: 2 Size Designator: 0 Duty Cycle: Intermittent Operating Voltage Characteristic: Full Outor emf acceleration Actuator Voltage: 110.0 ac Fuse Current Rating In Amps: 20.0 Load Protection Type: Overload Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: 18.0 18.0 Control Type:	Oa4483/fpn44, 45	
Fuse Accommodation Quantity:2Size Designator:0Duty Cycle:IntermittentOperating Voltage Characteristic:FullFullVoltage Restoring Method:Counter emf accelerationActuator Voltage:110.0 acFuse Current Rating In Amps:20.0Load Protection Type:OverloadInclosure Feature:Partially enclosedActional Electrical Manufacturers Association Standards Design:18.0Control Type:18.0Control Type:	Performance Type:	
2 Size Designator: 0 Duty Cycle: Intermittent Derating Voltage Characteristic: Full Full Voltage Restoring Method: Counter enf acceleration Actuator Voltage: 10.0 ac Fuse Current Rating In Amps: 20.0 Load Protection Type: Overload Inclosure Feature: Partially enclosed Attional Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0	Manual	
Size Designator:0Duty Cycle:IntermittentOperating Voltage Characteristic:FullFullFull Voltage Restoring Method:Counter emf accelerationActuator Voltage:110.0 acFuse Current Rating In Amps:20.0VoerloadInclosure Feature:Partially enclosedMatomal Electrical Manufacturers Association Standards Design:Designed per nema stdAmp Size Rating:18.0Contor Type:	Fuse Accommodation Quantity:	
0 Duty Cycle: Intermittent Operating Voltage Characteristic: Full Full Voltage Restoring Method: Counter emf acceleration Actuator Voltage: 10.0 ac Fuse Current Rating In Amps: 20.0 Fuse Current Rating In Amps: 20.0 Vorload Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Control Type:	2	
Duty Cycle: Intermittent Operating Voltage Characteristic: Full Full Full Voltage Restoring Method: Counter emf acceleration Actuator Voltage: 110.0 ac Fuse Current Rating In Amps: 20.0 Load Protection Type: Overload Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Courtor Type:	Size Designator:	
Intermittent Operating Voltage Characteristic: Full Full Voltage Restoring Method: Counter emf acceleration Actuator Voltage: 110.0 ac Fuse Current Rating In Amps: 20.0 Load Protection Type: Overload Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Control Type:	0	
Operating Voltage Characteristic:FullFull Voltage Restoring Method:Counter emf accelerationActuator Voltage:110.0 acFuse Current Rating In Amps:20.0Load Protection Type:OverloadInclosure Feature:Partially enclosedActional Electrical Manufacturers Association Standards Design:Designed per nema stdAmp Size Rating:18.0Control Type:	Duty Cycle:	
Full Full Voltage Restoring Method: Counter emf acceleration Actuator Voltage: 110.0 ac Fuse Current Rating In Amps: 20.0 Load Protection Type: Overload Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Control Type:	Intermittent	
Full Voltage Restoring Method:Counter emf accelerationActuator Voltage:110.0 acFuse Current Rating In Amps:20.0Load Protection Type:OverloadInclosure Feature:Partially enclosedNational Electrical Manufacturers Association Standards Design:Designed per nema stdAmp Size Rating:18.0Courcol Type:	Operating Voltage Characteristic:	
Counter emf acceleration Actuator Voltage: 110.0 ac Fuse Current Rating In Amps: 20.0 Load Protection Type: Overload Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0	Full	
Actuator Voltage:110.0 acFuse Current Rating In Amps:20.0Load Protection Type:OverloadInclosure Feature:Partially enclosedNational Electrical Manufacturers Association Standards Design:Designed per nema stdAmp Size Rating:18.0Control Type:	Full Voltage Restoring Method:	
110.0 ac Fuse Current Rating In Amps: 20.0 Load Protection Type: Overload Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Control Type:	Counter emf acceleration	
Fuse Current Rating In Amps:20.0Load Protection Type:OverloadInclosure Feature:Partially enclosedNational Electrical Manufacturers Association Standards Design:Designed per nema stdAmp Size Rating:18.0Control Type:	Actuator Voltage:	
20.0 Load Protection Type: Overload Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Control Type:	110.0 ac	
Load Protection Type:OverloadInclosure Feature:Partially enclosedNational Electrical Manufacturers Association Standards Design:Designed per nema stdAmp Size Rating:18.0Control Type:	Fuse Current Rating In Amps:	
Overload Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Control Type:	20.0	
Inclosure Feature: Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Control Type:	Load Protection Type:	
Partially enclosed National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Control Type:	Overload	
National Electrical Manufacturers Association Standards Design: Designed per nema std Amp Size Rating: 18.0 Control Type:	Inclosure Feature:	
Designed per nema std Amp Size Rating: 18.0 Control Type:	Partially enclosed	
Amp Size Rating: 18.0 Control Type:	National Electrical Manufacturers Association Standards Design:	
18.0 Control Type:	Designed per nema std	
Control Type:	Amp Size Rating:	
	18.0	
	Control Type:	

NSN 6110-00-932-4604

Motor Starter - Page 2 of 2

Features Provided:

Circuit protection fuse

Phase:

Single and three

Frequency In Hertz:

50.0

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A541c0

