

View Online at <https://aerobasegroup.com/nsn/6110-01-072-4447>

**Case Material:**

Aluminum alloy, qq-a-250/8, alloy 5052, h32 and plastic

**Case Surface Treatment:**

Chemical film, mil-c-5541, class 1a, alum only

**Connector Manufacturer Code:**

24930

**Connector Manufacturer Part Number:**

G350019s1 and g350019s2

**Maximum Voltage Rating In Volts:**

35.0 dc and 28.0 dc

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

0.1 and 3.0

**Terminal Location:**

Bottom

**Power Source:**

External

**Mounting Method:**

Rack

**Terminal Type And Quantity:**

2 connector, receptacle

**Maximumlength:**

14.500 inches

**Maximumwidth:**

5.750 inches

**Maximumheight:**

5.125 inches

**Special Features:**

Establishes the antenna control circuitry configuration in accordance with the mode selected by the scan mode switch and generates the azimuth-elevation switching and blanking gates

**Fsc Application Data:**

Receiver-transmitter, radar, nonairborne, except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A31700