NSN 6110-01-120-4593

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-120-4593

| Speed Adjustments: |
|--|
| 0 to full speed |
| Hazardous Locations/environmental Protection: |
| General purpose-nema type 1 |
| Overall Length: |
| 5.719 inches |
| |
| Overall Height: |
| 4.031 inches |
| Overall Width: |
| 3.500 inches |
| Ac Voltage Rating: |
| Between 200.0 volts and 575.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Manual |
| Performance Type: |
| Manual |
| Size Designator: |
| M-0 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Three slots for no. 10 mtg screws on isosceles 5-1/8 in. By 1-1/8 in. C to c |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 3.000 and 5.000 |
| Load Protection Type: |
| Overload and undervoltage |
| Inclosure Feature: |
| General purpose |
| National Electrical Manufacturers Association Standards Design: |
| Designed per nema std |
| Switch Functional Positions: |
| Start and stop |
| Control Type: |
| Local |
| Phase: |
| Three |
| Shelf Life: |

N/a

NSN 6110-01-120-4593

Motor Starter - Page 2 of 2



| | • • | | | | | | |
|----|-----|----|----|----|-----|----|----|
| ın | 1+ | Of | ΝЛ | ດລ | CI. | ır | ο. |
| | | | | | | | |

--

Demilitarization:

No

Fiig:

A541c0