## NSN 6110-01-123-3240

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-123-3240

| Speed Adjustments:  |
|---|
| 0 to full speed   |
| Hazardous Locations/environmental Protection:   |
| Dripproof and shock proof   |
| Overall Length:   |
| 8.500 inches  |
| Overall Height:   |
| 14.375 inches   |
| Overall Width:  |
| 12.000 inches   |
| Ac Voltage Rating:  |
| 440.0 volts   |
| Frequency Rating:   |
| 60.0 hertz  |
| Actuation Method:   |
| Magnetic  |
| Performance Type:   |
| Automatic   |
| Fuse Accommodation Quantity:  |
| 3   |
| Size Designator:  |
| 0   |
| Duty Cycle:   |
| Continuous  |
| Mounting Configuration:   |
| Four 15/32 in. Diameter mtg holes for 7/16 in. Diameter mtg bolts on 12-3/8 in. By 10 in. Mtg ctr |
| Operating Voltage Characteristic:   |
| Full  |
| Actuator Voltage:   |
| 440.0 ac  |
| Fuse Current Rating In Amps:  |
| 10.0  |
| Load Protection Type:   |
| Overload  |
| Ambient Temp:   |
| 50.0 degrees celsius  |
| Inclosure Feature:  |
| Fully enclosed  |
| National Electrical Manufacturers Association Standards Design:                                   |
| Designed per nema std   |
| Switch Functional Positions:  |

Close and emergency run and open and emergency close

## **NSN 6110-01-123-3240** Motor Starter - Page 2 of 2



| Control Type:           |
|-------------------------|
| Local                   |
| Features Provided:      |
| Circuit protection fuse |
| Phase:                  |
| Three                   |
| Frequency In Hertz:     |
| 60.0                    |
| Shelf Life:             |
| N/a                     |
| Unit Of Measure:        |
|                         |
| Demilitarization:       |

No Fiig: A541c0