## NSN 6110-01-138-5076

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-138-5076

## **Speed Adjustments:**

0 to full speed

## Hazardous Locations/environmental Protection:

Shock proof

## **Overall Height:**

13.000 inches

#### Ac Voltage Rating:

440.0 volts

## **Frequency Rating:**

60.0 hertz

## Actuation Method:

Magnetic

#### Performance Type:

Manual

#### Size Designator:

4

## Duty Cycle:

Continuous

#### **Mounting Configuration:**

Six mtg holes on 6-1/2 in. By 6-1/2 in. By 8 in. Mtg ctr

## **Operating Voltage Characteristic:**

Full

#### **Horsepower Rating:**

100.000

## Actuator Voltage:

440.0 ac

#### Load Protection Type:

Overload and undervoltage

#### Ambient Temp:

50.0 degrees celsius

#### **Inclosure Feature:**

Open

#### National Electrical Manufacturers Association Standards Design:

Designed per nema std

#### **Switch Functional Positions:**

Reset and start and stop

#### Control Type:

Local

## Phase:

Three

#### **Frequency In Hertz:**

60.0

# NSN 6110-01-138-5076

Motor Starter - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A541c0

