## NSN 6110-01-138-5078

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-138-5078

On and Additional transfer				
Speed Adjustments:				
0 to full speed				
Hazardous Locations/environmental Protection:				
Shock proof				
Overall Length:				
10.380 inches				
Overall Height:				
20.120 inches				
Overall Width:				
16.100 inches				
Ac Voltage Rating:				
440.0 volts				
Frequency Rating:				
60.0 hertz				
Actuation Method:				
Magnetic				
Performance Type:				
Automatic or manual				
Fuse Accommodation Quantity:				
2				
Size Designator:				
4				
Duty Cycle:				
Continuous				
Mounting Configuration:				
Four 17/32 in. Diameter mtg holes for 1/2 in. Mtg bolts on 18 in. By 12-1/2 in. Mtg ctr				
Operating Voltage Characteristic:				
Full				
Horsepower Rating:				
100.000				
Actuator Voltage:				
440.0 ac				
Fuse Current Rating In Amps:				
10.0				
Load Protection Type:				
Overload and undervoltage				
Ambient Temp:				
50.0 degrees celsius				
Inclosure Feature:				
Dripproof				
National Floctrical Manufacturers Association Standards Design:				

Designed per nema std

## NSN 6110-01-138-5078

Motor Starter - Page 2 of 2



Switch	Fun	ctions	I Pos	itions:

Automatic and emergency run and manual and off and reset and start and stop

**Control Type:** 

Local

**Features Provided:** 

Circuit protection fuse

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A541c0

Mil-std (military Standard):

Mil-c-2212 spec.