NSN 6110-01-145-2745

Motor Controller - Page 1 of 2

slow start and stop



View Online at https://aerobasegroup.com/nsn/6110-01-145-2745

Speed Adjustments:
Two speed
Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
24.000 inches
Overall Height:
11.000 inches
Overall Width:
22.000 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Automatic
Fuse Accommodation Quantity:
2
Size Designator:
0
Duty Cycle:
Continuous
Mounting Configuration:
Four 15/32 in. Diameter holes on 20-1/2 in. By 22 in. Rectangular mtg centers
Operating Voltage Characteristic:
Full
Actuator Voltage:
440.0 ac
Fuse Current Rating In Amps:
10.0
Load Protection Type:
Overload and undervoltage
Ambient Temp:
50.0 degrees celsius
Inclosure Feature:
Dripproof
National Electrical Manufacturers Association Standards Design:
Designed per nema std
Switch Functional Positions:

Emergency and emergency stop and fast and fast reset emergency run and fast start and run and slow and slow reset emergency run and

NSN 6110-01-145-2745

Motor Controller - Page 2 of 2



Control Type:
Local or remote
Features Provided:
Accessory location internal and circuit protection fuse
Phase:
Three
Special Features:
Accessory relay coil rated 115v 60 hz
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A541b0