NSN 6110-01-147-0654

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-147-0654

| 0 |
|--|
| Speed Adjustments: |
| 0 to full speed |
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 18.125 inches |
| Overall Height: |
| 9.765 inches |
| Overall Width: |
| 14.109 inches |
| Ac Voltage Rating: |
| 440.0 volts |
| Frequency Rating: |
| 60.0 hertz |
| Actuation Method: |
| Magnetic |
| Performance Type: |
| Manual |
| Fuse Accommodation Quantity: |
| 1 |
| Size Designator: |
| 1 |
| Duty Cycle: |
| Continuous |
| Mounting Configuration: |
| Four 17/32 in. Diameter holes rectangular arrangement 10-1/2 in. By 16 in. Centers |
| Operating Voltage Characteristic: |
| Full |
| Horsepower Rating: |
| 10.000 |
| Actuator Voltage: |
| 440.0 ac |
| Fuse Current Rating In Amps: |
| 10.0 |
| Load Protection Type: |
| Overload and undervoltage |
| Ambient Temp: |
| 50.0 degrees celsius |
| Inclosure Feature: |
| Dripproof |
| National Electrical Manufacturers Association Standards Design: |

Designed per nema std

NSN 6110-01-147-0654

Motor Starter - Page 2 of 2



Switch Functional Positions: Remote and reset and start and stop **Control Type:** Local or remote **Features Provided:** Circuit protection fuse Phase: Three **Special Features:** Remote halon switch not included Frequency In Hertz: 60.0 Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A541c0

Mil-c-2212 spec.

Mil-std (military Standard):