

View Online at <https://aerobasegroup.com/nsn/6110-01-147-0656>

Speed Adjustments:

0 to full speed

Hazardous Locations/environmental Protection:

Dripproof

Overall Length:

22.125 inches

Overall Height:

7.375 inches

Overall Width:

7.750 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

Performance Type:

Manual

Fuse Accommodation Quantity:

2

Size Designator:

0

Duty Cycle:

Continuous

Mounting Configuration:

Six 15/32 in. Diameter holes arranged in two parallel rows of three ea; 5-3/4 in. Spacing between rows; 9-1/4 in. Center to center spacing for holes

Operating Voltage Characteristic:

Full

Horsepower Rating:

0.500

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Dripproof

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Amp Size Rating:

18.0

Switch Functional Positions:

Reset and start and stop

Control Type:

Local

Features Provided:

Circuit protection fuse and accessory location internal

Phase:

Three

Special Features:

Accessory control power transformer rated 440 v primary 115 v secondary; 250 va; fused two 6 amp fuses

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A541c0

Mil-std (military Standard):

Mil-c-2212 spec.