

View Online at <https://aerobasegroup.com/nsn/6110-01-147-5610>

Speed Adjustments:

Two speed

Hazardous Locations/environmental Protection:

Dripproof

Overall Length:

32.125 inches

Overall Height:

11.765 inches

Overall Width:

24.125 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

Performance Type:

Automatic or manual

Fuse Accommodation Quantity:

3

Size Designator:

2

Duty Cycle:

Continuous

Mounting Configuration:

Eight 21/32 in. Diameter holes; rectangular arrangement; 2 rows of 4 ea; 7 in. C to c two interior holes; 6-3/4 in. C to c of end holes and interior holes; 30 in. Spacing between row centerlines

Operating Voltage Characteristic:

Full

Horsepower Rating:

25.000

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage and undervoltage release

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Dripproof

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Switch Functional Positions:

Automatic and emergency run and fast and fast reset emergency run and manual and off and remote and slow and slow reset emergency run and stop

Control Type:

Local or remote

Features Provided:

Circuit protection fuse

Phase:

Three

Special Features:

Reset pushbuttons for fast and slow overload included w/unit; all other switches provided by remote console not included w/unit

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541b0

Mil-std (military Standard):

Mil-c-2212 spec.