

View Online at <https://aerobasegroup.com/nsn/6110-01-147-5610>

**Speed Adjustments:**

Two speed

**Hazardous Locations/environmental Protection:**

Dripproof

**Overall Length:**

32.125 inches

**Overall Height:**

11.765 inches

**Overall Width:**

24.125 inches

**Ac Voltage Rating:**

440.0 volts

**Frequency Rating:**

60.0 hertz

**Actuation Method:**

Magnetic

**Performance Type:**

Automatic or manual

**Fuse Accommodation Quantity:**

3

**Size Designator:**

2

**Duty Cycle:**

Continuous

**Mounting Configuration:**

Eight 21/32 in. Diameter holes; rectangular arrangement; 2 rows of 4 ea; 7 in. C to c two interior holes; 6-3/4 in. C to c of end holes and interior holes; 30 in. Spacing between row centerlines

**Operating Voltage Characteristic:**

Full

**Horsepower Rating:**

25.000

**Actuator Voltage:**

440.0 ac

**Fuse Current Rating In Amps:**

10.0

**Load Protection Type:**

Overload and undervoltage and undervoltage release

**Ambient Temp:**

50.0 degrees celsius

**Inclosure Feature:**

Dripproof

**National Electrical Manufacturers Association Standards Design:**

Designed per nema std

**Switch Functional Positions:**

Automatic and emergency run and fast and fast reset emergency run and manual and off and remote and slow and slow reset emergency run and stop

**Control Type:**

Local or remote

**Features Provided:**

Circuit protection fuse

**Phase:**

Three

**Special Features:**

Reset pushbuttons for fast and slow overload included w/unit; all other switches provided by remote console not included w/unit

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541b0

**Mil-std (military Standard):**

Mil-c-2212 spec.