

View Online at <https://aerobasegroup.com/nsn/6110-01-147-7302>

Speed Adjustments:

Two speed

Hazardous Locations/environmental Protection:

Dripproof

Overall Length:

28.125 inches

Overall Height:

11.875 inches

Overall Width:

22.109 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

Performance Type:

Manual

Fuse Accommodation Quantity:

3

Size Designator:

3

Duty Cycle:

Continuous

Mounting Configuration:

Six 17/32 in. Diameter holes; rectangular arrangement; 2 rows 3 ea spaced 9-1/4 in. C to c; 26 in. Spacing between row centerlines

Operating Voltage Characteristic:

Full

Horsepower Rating:

40.000

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage and undervoltage release

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Dripproof

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Switch Functional Positions:

Emergency run and fast reset emergency run and forward and remote control off and reverse and slow reset emergency run and 1 and 2

Control Type:

Local or remote

Features Provided:

Reversible and circuit protection fuse

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A541b0

Mil-std (military Standard):

Mil-c-2212 spec.