

View Online at <https://aerobasegroup.com/nsn/6110-01-147-7302>

**Speed Adjustments:**

Two speed

**Hazardous Locations/environmental Protection:**

Dripproof

**Overall Length:**

28.125 inches

**Overall Height:**

11.875 inches

**Overall Width:**

22.109 inches

**Ac Voltage Rating:**

440.0 volts

**Frequency Rating:**

60.0 hertz

**Actuation Method:**

Magnetic

**Performance Type:**

Manual

**Fuse Accommodation Quantity:**

3

**Size Designator:**

3

**Duty Cycle:**

Continuous

**Mounting Configuration:**

Six 17/32 in. Diameter holes; rectangular arrangement; 2 rows 3 ea spaced 9-1/4 in. C to c; 26 in. Spacing between row centerlines

**Operating Voltage Characteristic:**

Full

**Horsepower Rating:**

40.000

**Actuator Voltage:**

440.0 ac

**Fuse Current Rating In Amps:**

10.0

**Load Protection Type:**

Overload and undervoltage and undervoltage release

**Ambient Temp:**

50.0 degrees celsius

**Inclosure Feature:**

Dripproof

**National Electrical Manufacturers Association Standards Design:**

Designed per nema std

**Switch Functional Positions:**

Emergency run and fast reset emergency run and forward and remote control off and reverse and slow reset emergency run and 1 and 2

**Control Type:**

Local or remote

**Features Provided:**

Reversible and circuit protection fuse

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541b0

**Mil-std (military Standard):**

Mil-c-2212 spec.