

View Online at <https://aerobasegroup.com/nsn/6110-01-148-4697>

Speed Adjustments:

0 to full speed

Hazardous Locations/environmental Protection:

Dripproof

Overall Length:

26.125 inches

Overall Height:

10.390 inches

Overall Width:

18.109 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Magnetic

Performance Type:

Automatic or manual

Fuse Accommodation Quantity:

6

Size Designator:

3

Duty Cycle:

Continuous

Mounting Configuration:

Six 17/32 in. Diameter holes; rectangular arrangement; 2 rows of 3 ea spaced 7-1/4 in. C to c; 24 in. Spacing between row centerlines

Operating Voltage Characteristic:

Full

Horsepower Rating:

50.000

Actuator Voltage:

110.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Dripproof

National Electrical Manufacturers Association Standards Design:

Designed per nema std

Switch Functional Positions:

Emergency run and lower and remote control off and raise and remote control on and start and stop

Control Type:

Local or remote

Features Provided:

Circuit protection fuse

Phase:

Three

Special Features:

Provides facility for switching electro-hydraulic power pump to alternate raise-lower modes of operation as distinct from motor reversal

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541c0

Mil-std (military Standard):

Mil-c-2212 spec.