## NSN 6110-01-149-2239

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-149-2239

On and Additional transfer
Speed Adjustments:
0 to full speed
Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
30.000 inches
Overall Height:
12.000 inches
Overall Width:
22.000 inches
Ac Voltage Rating:
440.0 volts
Frequency Rating:
60.0 hertz
Actuation Method:
Magnetic
Performance Type:
Manual
Size Designator:
5
Duty Cycle:
Continuous
Mounting Configuration:
Four 15/32 in. Diameter holes; rectangular pattern; on 20-1/2 in. By 28 in centers
Operating Voltage Characteristic:
Full
Horsepower Rating:
200.000
Actuator Voltage:
440.0 ac
Load Protection Type:
Overload and undervoltage
Ambient Temp:
50.0 degrees celsius
Inclosure Feature:
Dripproof
National Electrical Manufacturers Association Standards Design:
Designed per nema std
Switch Functional Positions:
Emergency run and reset and start and stop
Control Type:

Local

## NSN 6110-01-149-2239

Motor Starter - Page 2 of 2

A541c0



Phase:
Three
Special Features:
200 hp maximum at 440v 60hz 3 ph per nema size $5$
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: