# NSN 6110-01-149-2239

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-149-2239

# **Speed Adjustments:**

0 to full speed

# Hazardous Locations/environmental Protection:

Dripproof

# **Overall Length:**

30.000 inches

#### **Overall Height:**

12.000 inches

#### **Overall Width:**

22.000 inches

### Ac Voltage Rating:

440.0 volts

#### **Frequency Rating:**

60.0 hertz

#### **Actuation Method:**

Actuation

# Magnetic

Performance Type:

Manual

#### Size Designator:

5

#### Duty Cycle:

Continuous

#### Mounting Configuration:

Four 15/32 in. Diameter holes; rectangular pattern; on 20-1/2 in. By 28 in centers

#### **Operating Voltage Characteristic:**

Full

#### Horsepower Rating:

200.000

#### Actuator Voltage:

440.0 ac

#### Load Protection Type:

Overload and undervoltage

#### Ambient Temp:

50.0 degrees celsius

#### **Inclosure Feature:**

Dripproof

#### National Electrical Manufacturers Association Standards Design:

Designed per nema std

# **Switch Functional Positions:**

Emergency run and reset and start and stop

#### **Control Type:**

Local

# NSN 6110-01-149-2239

Motor Starter - Page 2 of 2



Phase:

Three

# **Special Features:**

200 hp maximum at 440v 60hz 3 ph per nema size 5

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A541c0