NSN 6110-01-149-2240

Motor Starter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6110-01-149-2240

Speed Adjustments:

0 to full speed

Hazardous Locations/environmental Protection:

Dripproof

Overall Length:

18.120 inches

Overall Height:

10.380 inches

Overall Width:

12.100 inches

Ac Voltage Rating:

440.0 volts

Frequency Rating:

60.0 hertz

Actuation Method:

Actuation

Magnetic

Performance Type:

Manual

Fuse Accommodation Quantity:

3

Size Designator:

1

Duty Cycle:

Continuous

Mounting Configuration:

Four 17/32 in. Diameter holes for 1/2 in. Mtg bolts

Operating Voltage Characteristic:

Full

Horsepower Rating:

10.000

Actuator Voltage:

440.0 ac

Fuse Current Rating In Amps:

10.0

Load Protection Type:

Overload and undervoltage

Ambient Temp:

50.0 degrees celsius

Inclosure Feature:

Dripproof

National Electrical Manufacturers Association Standards Design:

Designed per nema std

NSN 6110-01-149-2240

Motor Starter - Page 2 of 2



Switch Functional Positions:

Emergency run and off and run and start and stop

Control Type:

Local or remote

Features Provided:

Circuit protection fuse

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541c0

Mil-std (military Standard):

Mil-c-2212 spec.